



**ROLL-A-TEX
SAND TEXTURE ADDITIVE**

DESCRIPTION AND USES

Roll-A-Tex Sand Texture Additive is an extremely fine mineral compound that when added to paint will cover small cracks, hide tape joints, and will create a sand finish texture.

PERFORMANCE CHARACTERISTICS

- Create a sand finish texture to walls and ceilings
- Excellent for hiding cracks and tape joints
- Covers small cracks and hides patched surfaces
- Gives a fresh look to old plaster
- Works in all paints and varnishes
- Provides a durable, washable, texture coating

PRODUCTS

SKU	Description
22616	1-Pound
57608	8-Ounces

PRODUCT APPLICATION (cont.)

INSTRUCTIONS FOR USE

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85%. In a clean, separate container, add 4 ounces of Roll-A-Tex Additive to one quart of paint. More or less may be added for a rougher or finer surface. Mix thoroughly using a slotted paint paddle or mechanical agitator to ensure the additive is incorporated. Let the mixture sit for at least 30 minutes before applying. Stir occasionally to ensure good distribution of the mix. Use a 3/8" to 1/4" nap roller cover and follow the paint manufacturer's directions for application.

CLEAN-UP

Follow paint manufacturer's directions for clean up and disposal.

**TECHNICAL DATA****ROLL-A-TEX SAND TEXTURE ADDITIVE****PHYSICAL PROPERTIES**

Physical Properties		ROLL-A-TEX SAND TEXTURE ADDITIVE
Composition		Pumice, Crystalline Silica
Weight	Per Gallon	20.3 lbs.
	Per Liter	2.43 kg
Solids	By Weight	100.0%
	By Volume	100.0%
Volatile Organic Compounds		0 g/l
Shelf Life		5 years
Practical Coverage		Will depend on the method of application and surface type
Flash Point		>200°F (93°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.