

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM® EPOXYShield®

CONCRETE FLOOR PAINT

1-PART
ADVANCED ACRYLIC
TECHNOLOGY™

INTERIOR/EXTERIOR DURABILITY

HOT TIRE & CHEMICAL RESISTANT

SELF PRIMING - 1 COAT COVERAGE

UV & WEATHER RESISTANT

SOAP & WATER CLEAN-UP

USES:

- GARAGES
- CARPORTS
- DRIVEWAYS
- BASEMENTS
- PORCHES
- PATIOS
- WALKWAYS
- POOL DECKS

NET WT 128 FL OZ (3.79L)

ARMOR GRAY SATIN

ONE GALLON

EPOXYShield® CONCRETE FLOOR PAINT is a ready-to-use interior/exterior concrete floor paint specially formulated for use on garages, carports, driveways, basements, porches, patios, walkways and pool decks. A single coat of this self-priming concrete floor paint saves time and money, and Rust-Oleum's **ADVANCED ACRYLIC TECHNOLOGY™** resists damage from hot tires, motor oil, grease and gasoline. The durable, UV & weather-resistant satin finish is easy to maintain and resists fading and peeling, and the environmentally friendly formula can be easily cleaned up with soap & water.

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

WHERE TO USE: Use on interior or exterior concrete surfaces such as garage floors, carports, driveways, basements, porches, patios, walkways and pool decks. Allow newly poured concrete to cure for a minimum of 28 days prior to coating. Apply when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%. Not recommended for use on asphalt.

SURFACE PREPARATION:

Bare Concrete Surfaces: Proper surface preparation is critical to performance. Before coating bare concrete surfaces, remove grease, oil, salt and other contaminants with **EPOXYShield® HEAVY-DUTY DEGREASER**. Scrub spots thoroughly with a stiff bristle brush or broom and wipe up excess cleaner with rags or paper towels to keep contaminants from spreading. Rinse thoroughly with fresh water. Repeat as necessary to completely clean. If necessary, use a wire brush or sander to remove any loose or unsound concrete or masonry. For proper penetration and maximum adhesion, use **EPOXYShield® CONCRETE ETCH**. Follow label instructions carefully and allow the floor to dry completely. Wipe your fingers over the clean, dry surface. If you see any dust or powder on your fingers, repeat rinsing and scrubbing until the floor is clean.

Previously Painted, Stained or Sealed Concrete Surfaces: Use a wire brush to remove any loose or peeling paint, stain or sealer. To ensure proper adhesion, scuff sand the entire surface. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN YOUNG CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Rinse or sweep away dust and other particles. Wash the entire floor with **EPOXYShield® HEAVY-DUTY DEGREASER** (diluted as stated on the label) and scrub the surface using a stiff bristle brush or broom. Spot etch all exposed concrete surfaces using **EPOXYShield® CONCRETE ETCH**. Rinse thoroughly and allow to dry completely.

APPLICATION: **EPOXYShield® CONCRETE FLOOR PAINT** is ready to use. Do not thin. Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%. Do not paint outdoors if rain is expected within 48 hours. If using more than one gallon, intermix all cans of the same product to ensure color uniformity. Stir thoroughly before applying. Note: Painted floors may be slippery when wet. If desired, **EPOXYShield® ANTI-SKID ADDITIVE** may be added to the mixed coating. Use a brush or edger to trim the perimeter and hard-to-reach areas. Use a long handled roller and a high-quality, 1/2" nap roller cover to apply an even coat of **EPOXYShield® CONCRETE FLOOR PAINT** onto the surface. Apply in 4'x 4' sections, and maintain a wet edge to prevent lap marks and gloss differences. Continue applying in 4'x 4' sections until complete. Only one coat is necessary. If a second coat is desired, wait 24 hours before applying the second coat in a direction perpendicular to the first. Occasional touch-up may be necessary for areas subject to heavy vehicle traffic.

DRY TIME: Surface should be ready for light foot traffic in 12-16 hours and normal foot traffic in 24 hours. **FOR FULL CURE AND VEHICLE TRAFFIC, ALLOW 7 DAYS.** Dry times increase at cooler temperatures.

CLEAN UP: Wash tools and equipment with warm water and a mild detergent. Properly dispose of all soiled rags and protect unused product from freezing.

COVERAGE: Each gallon contains enough surface treatment to cover approximately 300-400 sq. ft. of smooth, bare concrete. Very rough or porous surfaces will require more material.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. **USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

¡ADVERTENCIA! ¡IRRITANTE! ES DAÑINO SI SE INGIERE. CONTIENE: ETILENGLICOL. PUEDE CAUSAR IRRITACION DE OJOS, NARIZ Y GARGANTA. EVITE EL CONTACTO CON LA PIEL Y OJOS Y EVITE RESPIRAR LOS VAPORES Y EL ROCÍO. UTILICE PROTECCIÓN PARA LOS OJOS Y ROPA PROTECTORA. **USAR ÚNICAMENTE CON VENTILACIÓN ADECUADA.** Para evitar respirar los vapores y el rocío, abra ventanas y puertas o use otras medidas para asegurar la entrada de aire fresco durante la aplicación y secado. Si siente lagrimeo, dolor de cabeza o mareo, incremente el aire fresco. Si se usa correctamente, un respirador (NIOSH aprobado para vapor orgánico, de serie P pre-filtrado particulado) podría ofrecer protección adicional; obtenga información profesional antes de usar. **PRIMEROS AUXILIOS:** Si tiene dificultad al respirar, alejese y obtenga aire fresco. Si continúan las dificultades obtenga ayuda médica de inmediato. En caso de contacto con los ojos, enjuague rápidamente con suficiente agua por lo menos 15 minutos y obtenga atención médica; para la piel, lave completamente con agua y jabón. Si se ingiere, obtenga atención médica de inmediato. **¡ADVERTENCIA!** Es sabido para el estado de California, que este producto contiene químicos que pueden causar cáncer y defectos al nacer u otros defectos reproductivos. **PRECAUCIÓN: NO SE DEJE AL ALCANCE DE LOS NIÑOS - NO LO INGIERA.**

Max VOC 250 g/L (2.08 lbs./gal.)

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Technical Support at 1-888-NUFLOOR (1-888-683-5667) for a full refund of the purchase price.

RUST-OLEUM®
CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061

An RPM Company

1-800-481-4785
rustoleum.com

COOL GARAGES.COM

©2006 Rust-Oleum Corporation
Made in USA 233996 0106

ARMOR GRAY 225359



0 20066 14044 1