



Stop Peeling Paint

Guide

Zinsser PEEL STOP



**BINDS PEELING,
FLAKING
AND CHALKING
SURFACES**

It's easy to Fix Problems

PEEL STOP® is a clear, flexible, binding sealer formulated for application to surfaces where peeling, chalking, and cracking are a problem. Even after painted surfaces have been scraped and sanded, tiny cracks and gaps remain under the edges of the old paint. PEEL STOP infiltrates these spaces and 'glues' them down, forming a tight bond that helps stop peeling. PEEL STOP penetrates and binds chalky residues. When applied over cracked or checked surfaces, PEEL STOP acts as a flexible bridging primer to seal face checking and prevent the finish coat from cracking, providing a sound surface for primer and paint.

PREVENT PAINT FAILURE:

- 1** **CLEAN & SCRAPE** surfaces thoroughly to remove as much loose, flaking, or powdery paint as possible.
 - Remove exterior mildew with ZINSSER's JOMAX® House Cleaner and Mildew Killer. Remove interior mildew with a commercial interior mildew cleaner.
 - 2** **APPLY** a liberal coat of PEEL STOP with a brush, roller, or airless sprayer.
 - 3** **WORK INTO** cracks and edges of old paint with brush or roller.
- One gallon of PEEL STOP will cover 300 to 400 square feet of surface, depending upon condition and porosity of substrate.
 - See product label or Technical Data Bulletin for complete instructions.


Tip...

For best results use a 100% acrylic topcoat paint.

How does Peel Stop Work?

Peeling paint is usually caused by moisture buildup, paint fatigue, or applying new paint over a chalky surface. PEEL STOP is a flexible, breathable sealer that seals and binds problem surfaces while allowing moisture to escape.

PEEL STOP bridges cracked and alligatored paint and remains flexible even in cold weather, helping to prevent the new paint from cracking and checking.



PEEL STOP glues down the edges of old paint, keeping them from popping and curling up after the primer and paint have been applied.



PEEL STOP penetrates chalky residues and binds them to the surface so the new paint and primer have a sound, firm surface for good adhesion.



Remember...

PEEL STOP is easy to use and is recommended for previously painted interior and exterior problem surfaces.

PEEL STOP®...

The name says it all™

Easy to apply with brush and roller to interior and exterior problem surfaces.



When dry, prime and topcoat with a quality latex or alkyd paint.



Latex formulation cleans up quickly and easily with soap and water.



Consult dealer for more information about Peel Stop, or other Zinsser products, visit www.rustoleum.com or call us at (800) 323-3584.

 **RUST-OLEUM**
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-323-3584

An **RPM** Company

©2014 RUST-OLEUM CORPORATION

280829 0114