



# KRUD KUTTER® GRAFFITI REMOVER

## DESCRIPTION AND USES

Krud Kutter® Graffiti Remover is a proprietary blend of biodegradable surfactants, detergents and emulsifiers that is designed to remove dried paints and stains on a variety of surfaces. It removes acrylic and acrylic enamel, aerosol paint, alkyd and polyurethane enamels, oil-based lacquers, primers, sealers, water-based enamels and also removes permanent markers, ink, lipstick, crayon and shoe dye.

Graffiti Remover is suitable for use on aluminum, brick, cinder block, concrete, fiberglass, formica, glass, metals, CMU, stainless steel, street signs, stucco, tile and terrazzo.

**IMPORTANT:** Test first on an inconspicuous area. May dull some painted surfaces. Not recommended for use on non-colorfast materials, woodwork, vinyl or plastic.

## PRODUCTS

SKU	DESCRIPTION
GR226	22 oz. Trigger Sprayer
GR326	32 oz. Trigger Sprayer
GR012	1-Gallon Bottle
GR05	5-Gallons
GR55	55-Gallon Drum

## PRODUCT APPLICATION

### DIRECTIONS FOR NON-POROUS SURFACES SUCH AS SIGNS & GLASS:

Thoroughly spray area damaged by graffiti and wait 3-5 minutes. Wipe off with a clean cloth or towel. Repeat if necessary.

### DIRECTIONS FOR POROUS SURFACES SUCH AS CONCRETE & BRICK:

Thoroughly spray area damaged by graffiti and wait 5-10 minutes. Use a brush to agitate and loosen graffiti. Hose off with water or use pressure washer. Repeat if necessary.

**WARNING: MAY BE HARMFUL IF INHALED, ABSORBED THROUGH THE SKIN OR SWALLOWED.** Mist or vapors may be irritating to the eyes, nose, throat and lungs. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. **Do not induce vomiting.** Get medical attention.

**KEEP OUT OF REACH OF CHILDREN.**

	<b>TECHNICAL DATA</b>	<b>KRK-04</b>
	<b>KRUD KUTTER® GRAFFITI REMOVER</b>	

## PHYSICAL PROPERTIES

	GRAFFITI REMOVER
<b>Composition</b>	Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers
<b>Color</b>	Clear
<b>pH</b>	NA
<b>VOC</b>	9%
<b>Practical Coverage</b>	16 ounces – 25-37 square feet
	22 ounces – 35-50 square feet
	32 ounces – 50-75 square feet
	1-Gallon – 200-300 square feet
<b>Shelf Life</b>	NA
<b>Flash Point</b>	200°F (93°C)
<b>Caution!</b>	<b>WARNING: MAY BE HARMFUL IF INHALED, ABSORBED THROUGH THE SKIN OR SWALLOWED.</b> Mist or vapors may be irritating to the eyes, nose, throat and lungs. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. <b>Do not induce vomiting.</b> Get medical attention. <b>KEEP OUT OF REACH OF CHILDREN.</b>
<b>Safety Information</b>	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061

Phone: 877-385-8155  
www.rustoleum.com

Form: GDH-523  
Rev.: 080421