

	TECHNICAL DATA	ROC-214
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM®	RUST-OLEUM® ANTI-SKID ADDITIVE	

DESCRIPTION AND USES

Rust-Oleum® Anti-Skid Additive is an aluminium oxide based anti-skid additive designed to provide skid resistance when added to epoxy, latex or oil based paints or stains to concrete, wood, metal or fibreglass. Anti-Skid Additive will not change the performance or properties of the coatings when added at the recommended level.

PRODUCT

SKU	DESCRIPTION
374282	227g

APPEARANCE

Sand-like particles

PRODUCT APPLICATION

MIXING

For one part floor coatings: Add one package for each 3.78L of coating just prior to application. Pour the additive in slowly, while stirring and mix thoroughly until the additive is evenly dispersed.

For two part floor coatings: Premix both components to re-disperse any settled particles; then add the activator to the base. If there is an induction time for the product, allow the coating to stand the recommended amount of time. Then pour the additive in slowly, while stirring and mix thoroughly until the additive is evenly dispersed.

APPLICATION

Apply the coating as normal. Remix the paint in the can several times during use to ensure that any settled Anti-Skid Additive is re-incorporated into the coating. If applying more than one coat of paint, mix the Rust-Oleum Anti-Skid Additive into the final coat only.

PHYSICAL PROPERTIES

		ANTI-SKID ADDITIVE
Composition		Aluminum Oxide
Weight	Per Gallon	33.0 lbs.
	Per Liter	3.95 kg
Solids	By Weight	100%
	By Volume	100%
Volatile Organic Compounds		0
Shelf Life		Unlimited
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



RUST-OLEUM AUSTRALIA & NEW ZEALAND
PTY LTD
Level 2, 307 Ferntree Gully Road
Mount Waverley, Victoria 3149 Australia
PH: 1 300 784 476
Email: technical@rustoleum.com.au
www.rustoleum.com.au

Rust-Oleum New Zealand
Quad 7 Level 1, 6 Leonard Isitt Drive
Auckland Airport, Auckland 2022 New Zealand
PH: 0800 787 865
Email: technical@rustoleum.co.nz
www.rustoleum.co.nz

Rust-Oleum South Africa PTY. LTD
PO Box 400 Randvaal 1873
Gauteng, South Africa
PH: 016 365 5120
Email: info@rustoleum.co.za
www.rustoleum.co.za

Form: ARJ-2217
Rev.: 050721