

MILK PAINT
FINISH
FOR DÉCOR & FURNITURE

RUST-OLEUM®
MILK PAINT FINISH

DESCRIPTION AND USES

Rust-Oleum® Milk Paint Finish creates a unique washed effect, perfect for furniture and décor pieces. This one-step paint finish is easy to use and has superior adhesion. Multiple coats can be applied to achieve desired effect.

PRODUCTS

SKU	DESCRIPTION (946 mL)
346263	Navy
346265	Kensington Grey
346260	Highland Blue
246264	Eclipse
246266	Classic White
346267	Venetian Yellow

APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water and let dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Remove any wax by lightly wiping the surface with mineral spirits.

PRIMING

Priming is not required for most surfaces. For superior coverage, a Rust-Oleum® primer can be used for surfaces such as bare wood and treated wood.

APPLICATION (cont.)

APPLICATION

For interior use only. Do not apply paint on surfaces which are exposed to high humidity. Use when temperature is between 10°C and 32°C and humidity is below 85% to ensure proper drying.

Stir well before use. A high quality synthetic brush is recommended for application. Apply a light coat to your surface, brushing in a “V” pattern to achieve a washed look. Apply multiple coats to achieve a washed look. If applying to wood, brush in the direction of the wood grain.

NOTE: Paint finish will have a subtle texture. For full coverage, apply multiple coats. For added protection, use Rust-Oleum® Chalked Paint Matt Clear Protective Top Coat.

DRY AND RECOAT TIMES

Based on 25°C 50% relative humidity. Dries to the touch in 30-60 minutes. May be recoated after 1 hour. Allow more time at cooler temperatures or in high humidity.

COVERAGE

946 mL will cover up to 9m², depending on surface texture, porosity, and application method.

CLEAN UP

Clean brush and other application tools with soap and water. Clean up any drips or spills immediately.

DISPOSAL

To dispose of empty containers and unused product, contact your local environmental regulatory agency.

**MILK PAINT
FINISH**
— FOR DÉCOR & FURNITURE —

**RUST-OLEUM®
MILK PAINT FINISH**

PHYSICAL PROPERTIES

		MILK PAINT FINISH
Resin Type		Acrylic
Pigment Type		Varies depending on color
Solvents		Water, Glycol Ethers
Weight	Per Gallon	10.6-12 lbs.
	Per Liter	1.3-1.4 kg
Solids	By Weight	46.6-56.28%
	By Volume	32.12-37.27%
Volatile Organic Compounds		<110 g/l
Recommended Dry Film Thickness (DFT) per Coat		1-2 mils
Wet Film to Achieve DFT (Unthinned material)		5-6 mils
Practical Coverage at Recommended DFT (assume 15% material loss)		946 mL will cover up to 9m ²
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	30-60 minutes
	Recoat	1 hour
	Full Cure	24 hours
Shelf Life		3 years
Flash Point		>93°C
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia PTY. LTD
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
Email: sales@rustoleum.au
www.rustoleum.com/au

Rust-Oleum New Zealand
Quad 7 Level 1, 6 Leonard Isitt Drive
Auckland Airport, Auckland 2022 New Zealand
PH: 0800 787 865
Email: technical@rustoleum.co.nz
www.rustoleum.co.nz

Rus-Oleum South Africa PTY. LTD
PO Box 400 Randvaal 1873
Gauteng, South Africa
PH: 016 365 5120
Email: info@spraymate.co.za
www.rustoleum.co.za

Form: ARJ-1683
Rev.: 100918