



**CHALKED  
PROTECTIVE TOPCOAT**

**DESCRIPTION AND USES**

Rust-Oleum® Chalked Clear Protective Topcoat enhances any Chalked Ultra Matt Paint finish and adds protection to the surface. The clear topcoat can be applied to maintain and enhance any Chalked project. It also protects from the elements and is recommended for high traffic areas. It is easier to apply and has more durability compared to traditional furniture waxes. **For interior use only.**

**PRODUCTS**

SKU	DESCRIPTION
305203	Matt Clear Topcoat

**PAINTING CONDITIONS**

Use in a well ventilated area when temperature is between 10°C and 32°C and humidity is below 85% to ensure proper drying.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Stir thoroughly. Do not shake the can. Thinning is not required. Avoid painting in direct sunlight or on hot surfaces.

Use a high quality synthetic brush. Roller application is not recommended. Avoid excessive brushing as this will reduce film thickness and protection. Wait for the base coat to dry for at least 8 hours before applying the Clear Protective Topcoat. Use light even brush strokes to ensure even flow and the smoothest finish. Apply 1-2 even coats. Wait 2 hours between each coat.

**DRY & RECOAT**

Dry and recoat times are based on 25°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 30 minutes, to handle in 1 hour and is fully dry in 4 hours. May be recoated after 2 hours.

**CLEAN-UP**

Clean brush and other and application tools with soap and water.

**COVERAGE**

Up to 14 square metres.

**TECHNICAL DATA**

**CHALKED PROTECTIVE TOPCOAT**

**PHYSICAL PROPERTIES**

		CHALKED PROTECTIVE TOPCOAT
<b>Resin Type</b>		Acrylic Urethane
<b>Pigment Type</b>		NA
<b>Solvents</b>		Water and Glycol Ethers
<b>Weight</b>	<b>Per Litre</b>	1.02 kg
	<b>Per Gallon</b>	8.50 lbs.
<b>Solids</b>	<b>By Weight</b>	30.5%
	<b>By Volume</b>	28.8%
<b>Volatile Organic Compounds</b>		<250 g/l
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		25-50µ (1.0-2.0 mils)
<b>Wet Film to Achieve DFT</b>		100-150µ (4.0-6.0 mils)
<b>Practical Coverage at Recommended DFT</b>		14 square metres
<b>Dry Times at 21-27°C and 50% Relative Humidity</b>	<b>Touch</b>	30 minutes
	<b>Handle</b>	1 hour
	<b>Fully Dry</b>	4 hours
<b>Shelf Life</b>		3 years
<b>Flash Point</b>		(93°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.