

**TECHNICAL DATA****ZNR-86****ZINSSER® PAINTBOOSTER™ FLOW CONTROL  
ADDITIVE FOR WATER-BASE PAINTS****DESCRIPTION AND USES**

Zinsser® PaintBooster™ Flow Control Paint Additive for Water-based Paints is designed to make painting easier by improving paint flow and eliminating brush & roller marks. It is formulated for today's low VOC paints by extending the "wet edge" working time without changing the coating's cure time, colour, sheen or flexibility.

PaintBooster is ideal for painting in hot, dry climates and spray applications. . One 946 mL will treat up to 57 litres of paint.

Use PaintBooster with water-based coatings including latex paints & primers, water reducible oil/alkyds and waterborne varnishes and epoxies.

**PRODUCT****SKU DESCRIPTION**

379270 946 mL

**PRODUCT APPLICATION****DIRECTIONS**

Mix or shake well before use. Add 59 mL (4 capfuls) per 3.78 L of paint. For very low VOC coatings, faux finishing or in hot, dry climates add more PaintBooster not exceeding 177mL per 3.78L. Always check for product compatibility before proceeding with a job. Close container after each use. Clean up spills with water.

**PRODUCT APPLICATION (cont.)****DIRECTIONS (cont.)**

PaintBooster for Water-based Paints does not change the topcoat colour, sheen or flexibility. One dose of PaintBooster adds only 1 g/l VOC to most water-based coatings, making it ideal for very low VOC paints. Close container after each use.

**CLEAN-UP**

Clean up tools and equipment according to the paint manufacturer's directions. If spilled, contain the material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**WARNING:** If swallowed, **DO NOT** induce vomiting. CALL A PHYSICIAN IMMEDIATELY. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water.

**KEEP OUT OF REACH OF CHILDREN.**

**\*Note:** Paint additives are not subject to architectural coating VOC regulations. However, one dose of PaintBooster adds no more than 1 g/l VOC to most water-based coatings. Always check local VOC regulations.

**PHYSICAL PROPERTIES**

PAINT ADDITIVE FOR WATER-BASED PAINTS		
Composition		Water-based Proprietary Additive, Propylene Glycol, Water
Weight	Per Gallon	8.34 lbs.
	Per Liter	1.00 kg
VOC (Weight %)		0.8%
Shelf Life		5 years
Flash Point		100°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



RUST-OLEUM AUSTRALIA & NEW ZEALAND  
PTY LTD  
Level 2, 307 Ferntree Gully Road  
Mount Waverley, Victoria 3149 Australia  
PH: 1 300 784 476  
Email: [technical@rustoleum.com.au](mailto:technical@rustoleum.com.au)  
[www.rustoleum.com.au](http://www.rustoleum.com.au)

Rust-Oleum New Zealand  
Quad 7 Level 1, 6 Leonard Isitt Drive  
Auckland Airport, Auckland 2022 New Zealand  
PH: 0800 787 865  
Email: [technical@rustoleum.co.nz](mailto:technical@rustoleum.co.nz)  
[www.rustoleum.co.nz](http://www.rustoleum.co.nz)

Rust-Oleum South Africa PTY. LTD  
PO Box 400 Randvaal 1873  
Gauteng, South Africa  
PH: 016 365 5120  
Email: [info@rustoleum.co.za](mailto:info@rustoleum.co.za)  
[www.rustoleum.co.za](http://www.rustoleum.co.za)

Form: ARJ-2269  
Rev.: 093021