



# RUST-OLEUM® CUSTOM MATT PREMIUM LACQUER PAINT

## DESCRIPTION AND USES

Rust-Oleum® Custom Automotive Paint is a premium automotive lacquer designed to give an on-trend, durable finish. The matt sheen creates a smooth finish with a soft glow, making it perfect for automotive accent projects like interiors, wheels and striping. With long lasting protection and durability, smudge resistance, and great coverage for quick project completion.

**NOTE:** Do not use Rust-Oleum Custom Lacquer over existing air-dried enamel paints.

## PRODUCTS

SKU	DESCRIPTION (Aerosol)
376135	Matt Black
376136	Matt Pearl White
376137	Matt Emeral Green
376148	Matt Orange
376149	Matt Red
376150	Matt Blue
376151	Matt Clear

## PRODUCT APPLICATION

### SURFACE PREPARATION

Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry.

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### PRIMING

Use of a Primer provides added corrosion protection, better adhesion and hiding. It is especially recommended for porous surfaces and metal.

## PRODUCT APPLICATION (cont.)

### APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 10-32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 93°C or galvanised metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If the mixing ball fails to rattle, DO NOT STRIKE. Contact Rust-Oleum. Shake often during use. Hold can upright 25-30cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart. **Do not use near open flame.**

### DRY AND RECOAT

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, fully dry in 24 hours. Apply a second coat any time. Apply a clear top coat for maximum durability.

### CLEAN UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with xylol or acetone. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

### CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as acetone. Do not stick a pin or other objects into the stem.



**RUST-OLEUM® CUSTOM MATT  
PREMIUM LACQUER PAINT**

**PHYSICAL PROPERTIES**

		MATT PREMIUM LACQUER PAINT
<b>Resin Type</b>		Acrylic
<b>Pigment Type</b>		Varies with colour
<b>Solvents</b>		Ketones, Dimethyl Carbonate
<b>MIR</b>		0.95 max
<b>Fill Weight</b>		312g.
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		1.5–2.5 mils
<b>Dry times at 25°C and 50% Relative Humidity</b>	<b>Touch</b>	20 minutes
	<b>Handle</b>	30 minutes
	<b>Recoat</b>	Anytime
<b>Shelf Life</b>		5 years
<b>Dry Heat Resistance</b>		93°C
<b>Flash Point</b>		-104°C
<b>Safety Information</b>		For Additional Information, See SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



RUST-OLEUM AUSTRALIA & NEW ZEALAND  
PTY LTD  
Level 2, 307 Ferntree Gully Road  
Mount Waverley, Victoria 3149 Australia  
PH: 1 300 784 476  
Email: [technical@rustoleum.com.au](mailto:technical@rustoleum.com.au)  
[www.rustoleum.com.au](http://www.rustoleum.com.au)

Rust-Oleum New Zealand  
Quad 7 Level 1, 6 Leonard Isitt Drive  
Auckland Airport, Auckland 2022 New Zealand  
PH: 0800 787 865  
Email: [technical@rustoleum.co.nz](mailto:technical@rustoleum.co.nz)  
[www.rustoleum.co.nz](http://www.rustoleum.co.nz)

Rust-Oleum South Africa PTY. LTD  
PO Box 400 Randvaal 1873  
Gauteng, South Africa  
PH: 016 365 5120  
Email: [info@rustoleum.co.za](mailto:info@rustoleum.co.za)  
[www.rustoleum.co.za](http://www.rustoleum.co.za)

Form: ARJ-2231  
Rev.:062821