

• TRUSTED QUALITY SINCE 1921 •



**RUST-OLEUM®  
DECORATIVE COLOUR CHIPS**

**DESCRIPTION AND USES**

Rust-Oleum® Decorative Chips are designed for use with any one-part or two-part concrete floor coating. When sprinkled onto a freshly coated surface, these decorative chips bond to the wet film to become a permanent part of the coating.

Rust-Oleum Decorative Chips also help hide dirt and surface imperfections and can be used with water-based or solvent-based concrete coatings.

For use in: garages, carports, laundry rooms, basements, porches, patios, walkways and pool decks.

**PRODUCT**

SKU	DESCRIPTION (454g Bag)
374283	Grey Blend

**PRODUCT APPLICATION**

Do not mix Decorative Chips into the coating. Apply concrete floor coating (sold separately) in 1.2m x 1.2m sections. Immediately after completing the final roller passes, begin broadcasting the Decorative Chips onto the wet coating. Distribute the Decorative Chips by tossing them up into the air above the coating in an underhand manner. This allows the chips to drop directly down onto the surface of the coating. Avoid slinging the chips onto the coating with a sidearm throw.

**IMPORTANT: Apply decorative chips to wet paint only.**

Move on to the next 1.2m x 1.2m section and continue until complete.

**Note:** Fresh paint can be applied over the loose chips that lay outside the previously painted area. For a high gloss finish, topcoat garage floors with EpoxyShield® Premium Series Clear Finish.

**COVERAGE**

Standard Chip Pattern – 23m<sup>2</sup> per bag  
Heavy Chip Pattern – 12m<sup>2</sup> per bag

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



RUST-OLEUM AUSTRALIA & NEW ZEALAND  
PTY LTD  
Level 2, 307 Ferntree Gully Road  
Mount Waverley, Victoria 3149 Australia  
PH: 1 300 784 476  
Email: [technical@rustoleum.com.au](mailto:technical@rustoleum.com.au)  
[www.rustoleum.com.au](http://www.rustoleum.com.au)

Rust-Oleum New Zealand  
Quad 7 Level 1, 6 Leonard Isitt Drive  
Auckland Airport, Auckland 2022 New Zealand  
PH: 0800 787 865  
Email: [technical@rustoleum.co.nz](mailto:technical@rustoleum.co.nz)  
[www.rustoleum.co.nz](http://www.rustoleum.co.nz)

Rust-Oleum South Africa PTY. LTD  
PO Box 400 Randvaal 1873  
Gauteng, South Africa  
PH: 016 365 5120  
Email: [info@rustoleum.co.za](mailto:info@rustoleum.co.za)  
[www.rustoleum.co.za](http://www.rustoleum.co.za)

Form: ARJ-2216  
Rev.: 051721