



2X ULTRA COVER METALLIC ROSE GOLD

DESCRIPTION AND USES

Rust-Oleum® 2x Ultra Cover Metallic Rose Gold Spray is designed to provide twice the coverage on wood, metal, most plastic, wicker and more. It covers surfaces with less spray passes which allows projects to be completed faster and easier. The comfort spray tip with a wider finger pad reduces fatigue caused by continuous spraying.

Some plastics made of polyethylene such as Little Tikes® children's products are manufactured in a way that may hinder maximum paint adhesion. Test this product in an inconspicuous area to test for compatibility on the surface.

PRODUCTS

SKU	DESCRIPTION
310419	Metallic Rose Gold

PRODUCT APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 10°C and 32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

PRODUCT APPLICATION (cont.)

PRIMING

Use of Rust-Oleum® 2X Ultra Cover Primer will optimize adhesion and hiding and is recommended for bare wood and metal.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 25-40 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. For best appearance, apply one light coat followed by one heavier (wet) coat. Do not use near open flame.

DRY & RECOAT TIMES

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 10 minutes and to handle in 30 minutes. Recoat within 1 hour or after 48 hours. For added protection a clear top coat is recommended. NOTE: On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

COVERAGE

Up to 4.5 m² per can, depending on surface.

CLEAN-UP

When finished spraying, clear spray valve by turning the can upside down and pushing the spray button for 5 seconds. Clean-up wet paint with mineral turps. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not stick pin or any other object into the stem.

* Little Tikes® is a registered trademark of The Little Tikes Company.



TECHNICAL DATA

2X ULTRA COVER METALLIC ROSE GOLD

PHYSICAL PROPERTIES

		METALLIC ROSE GOLD
Resin Type		Acrylic Modified Alkyd
Pigment Type		Copper Flake, Aluminum Flake
Solvents		Acetone, N-Butyl Acetate, Dimethyl Carbonate, Naphtha, Xylene
MIR		1.25 Max
Fill Weight		312 grams
Recommended Dry Film Thickness (DFT) per Coat		25-50µ
Practical Coverage at Recommended DFT (assumes 15% material loss)		4.5 m ² /can
Dry Times at 21-27°C (70-80°F) and 50% Relative Humidity	Touch	10 minutes
	Handle	30 minutes
	Recoat	Within 1 hour or after 48 hours
Dry Heat Resistance		93°C
Shelf Life		5 years
Flash Point		-104°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia Pty, Ltd.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766
PH: 1 300 784 476
www.rustoleum.com.au
email: sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 4325
Christchurch, New Zealand
PH: 64 3 384 3210
email: mail@haydn.co.nz

Form: GDH-1119
Rev.: 081417