CAUTION

KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTIONS

SAFETY DIRECTIONS: Use only in a well-ventilated area. Do not breathe vapours. May irritate eves and skin. Do not get in eyes. on skin or clothing.

FIRST AID INSTRUCTIONS

General: In all doubt, or when symptoms persist, seek medical advice immediately.

Inhalation: Remove affected person to fresh air. Get medical attention for any breathing difficulty.

Skin: Wash thoroughly with water and soap. Remove any contaminated clothing and wash before re-use. If irritation occurs consult a doctor.

Eyes: In case of eye contact, rinse immediately with plenty of water for at least 15 minutes. See a doctor if irritation persists.

Ingestion: If swallowed, immediately contact a Poison Centre (Phone: AUS 13 11 26; NZ 0800 764 766) or a doctor. Do NOT induce vomiting.

For further information, refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz





Rust-Oleum® Metallic Varnish is a one-of-a-kind metallic effect and a durable scratch-resistant finish in one. Create a translucent metallic look over any stained, painted or unfinished surface. Apply one or more coats to achieve a unique, custom look. Ideal for furniture, cabinetry, accessories and more. The final look will be unique — determined by the original colour and number of coats applied. Metallic Varnish offers superior scratch resistance in a clear semi-gloss finish. The water-based formula is virtually odourless, fast drying, and provides for easy soap and water clean-up.

RECOMMENDED FOR: Furniture, cabinets, trim, doors, accessories and more.

NOT RECOMMENDED FOR: Floors or outdoor surfaces.

PREPARATION:

PREVIOUSLY FINISHED SURFACES: For best adhesion, surfaces must be clean, dry, and free of old finishes, dust, dirt, oils, or foreign matter. Sand surface using 150-220 grit sandpaper and remove all sanding dust using a vacuum or a tack cloth. Do NOT use steel wool as rust may develon after finish has been applied.

STAINED OR PAINTED WOOD: Follow manufacturer's direction for application of stain or paint. Make certain surface is thoroughly dry before applying Rust-Oleum Metallic Varnish. For best results, use Rust-Oleum® Wood Stains.

UNFINISHED SURFACES: Sand using 150-220 grit sandpaper and remove all sanding dust using a vacuum or a tack cloth. If a filler or putty is used, make sure that it does not contain wax and allow for enough time to dry thoroughly. APPLICATION: Stir the contents thoroughly before use. DO NOT SHAKE. Apply with a high-quality, synthetic bristle brush or a foam brush in the direction of the grain. Apply in a thin coat until a uniform film has been achieved. To prevent brush marks, avoid excessive brushing. A minimum of 2 coats are recommended. Very lightly sand between coats with 320 grit sandpaper. Do not use steel wool. Additional coats will enhance the metallic effects and can be applied with one hour dry time between coats. Allow 48 hours to cure before moderate use of project. Allow 7 days for total cure of project.

COVERAGE: Approximately 9-11m² per 946 mL. Coverage may vary depending on the applicator and wood species

used.

CLEAN UP: Clean application tools and equipment with soap and water. STORAGE: Store locked up. Keep from freezing.



RUST-OLEUM AUSTRALIA PTY. LTD. Unit 12, 4 Southridge Street Eastern Creek, NSW 2766 Australia PH: 1 300 784 476

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

©2018 Rust-Oleum Corporation Made in USA 337905 0118