




# EXTREME ADHESION PRIMER

## Urethane Modified Acrylic

For the hardest to stick-to surfaces

- Guaranteed to bond
- Superior adhesion and hardness
- Fast curing
- Works with all top coats

FORMULATED WITH X-IM TECHNOLOGY




### BONDS TO:

- Wood
- Porcelain Tiles
- Glass
- Metals
- Most Plastics
- Fibreglass
- Laminate

### CAUTION!

Read caution statements on back panel.



**Extreme Adhesion Primer** is a water-based bonder that has both primer and adhesive-like properties. It provides excellent adhesion to "hard-to-paint" surfaces even in high humidity conditions. Extreme Adhesion Primer will form a hard film when fully cured. Extreme Adhesion Primer resistance to scratch testing can vary with the type of surface and the degree of cure, however, when fully cured, it will provide long lasting adhesion for these "hard-to-paint" surfaces. It must be top coated.

**SURFACES:** Use Extreme Adhesion Primer on wood, metal, most plastics, fibreglass, laminate, tile, porcelain, glazed block, glass. Also recommended for Kynar® and Silicone Polyester siding. Note: Because there are many types of surfaces, plastics and composites, always test a small area for adhesion and top coat compatibility before starting. When priming Kynar® or Silicone Polyester pre-painted siding at least two test patches in different areas is a must to demonstrate adhesion that is acceptable to you.

**SURFACE PREPARATION:** Surface should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion. If unsure, wash surface with an appropriate cleaner, ammonia or a TSP substitute. Rinse thoroughly and allow to dry. Kill any mould and mildew. Spot prime knots or severe water stains with Zinsser BIN® Primer Sealer. On exteriors, countersink exposed nail heads, spot-prime and fill with spackling compound. Wire brush rusty areas. Clean new galvanised metal with solvent cleaner.

**APPLICATION:** Extreme Adhesion Primer may be applied by synthetic fibre brush, 6.35 mm synthetic fibre roller or by spraying. The temperature of air and surface can be as low as 4°C or up to 38°C. Extreme Adhesion Primer can be top coated in 3 hours (will vary with temperature). When top coating with 2 component paints, allow 24 hours before painting. If possible, plan your painting to avoid rain, moisture and high humidity for the first 24 hours of curing. Painting flexible caulks or seams can result in cracks in the paint film. Caulk seams and edges after painting.

**TINTING:** If tinting, use up to a maximum of 59ml of universal tint per 3.78L.

**COVERAGE:** Extreme Adhesion Primer covers about 41.8m<sup>2</sup>/3.78L.

**DRY TIME:** Extreme Adhesion Primer dries to touch in about 30 to 45 minutes and will reach full hardness in 7 to 10 days depending on temperature, humidity and film thickness. It can be lightly sanded after about 3 hours after application. Extreme Adhesion Primer can be used for indoor and outdoor applications, and can be top coated with all top coats including latex, oil alkyds, lacquers, urethanes and epoxies.

**CLEANUP:** Clean equipment immediately after use with soap and water. Clean spatters or spills immediately with warm water.

**LIMITATIONS:** Not recommended for sinks, tubs or showers where continuous water or hot water contact occurs. Not recommended for use on polyethylene or polypropylene. Not recommended for below grade application.

For further application instructions refer to the Technical Data Sheet available at [www.rustoleum.com.au](http://www.rustoleum.com.au) or [www.rustoleum.co.nz](http://www.rustoleum.co.nz) or [www.rustoleum.co.za](http://www.rustoleum.co.za)

### CAUTION

**KEEP OUT OF REACH OF CHILDREN**

**READ SAFETY DIRECTIONS BEFORE OPENING OR USING**

**DO NOT SWALLOW**

**SAFETY DIRECTIONS:** Use only in well-ventilated areas. Avoid contact with skin and eyes and inhalation of vapour, spray or mist. Wear protective gloves. Keep container tightly closed and in a well ventilated area.

### FIRST AID:

**General:** In all doubt, or when symptoms persist, seek medical advice immediately. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical attention for any breathing difficulty.

**Skin:** Wash thoroughly with water and soap. Remove any contaminated clothing. Wash contaminated clothing before re-use. If irritation occurs consult a doctor.

**Eyes:** In case of eye contact, rinse immediately with plenty of water for at least 15 minutes. See a doctor if irritation persists.

**Ingestion:** If swallowed do NOT induce vomiting. For advice, contact a Poisons Information Centre (Poison Centre Phone: **AUS** 13 11 26; **NZ** 0800 764 766; **SA** 086 155 5777) or a doctor at once.

For further information refer to the Safety Data Sheet available at [www.rustoleum.com.au](http://www.rustoleum.com.au) or [www.rustoleum.co.nz](http://www.rustoleum.co.nz) or [www.rustoleum.co.za](http://www.rustoleum.co.za)

**MANUFACTURED BY:** Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, Illinois 60061, USA. **IMPORTED AND/OR DISTRIBUTED BY:** **AUSTRALIA:** RUST-OLEUM AUSTRALIA & NEW ZEALAND PTY LTD 8 Lakeview Drive Scoresby, Melbourne, Victoria 3179 Australia; PH: 1 300 784 476; email: [sales@rustoleum.com.au](mailto:sales@rustoleum.com.au), [www.rustoleum.com.au](http://www.rustoleum.com.au); **NEW ZEALAND:** Rust-Oleum New Zealand, Quad 7 Level 1, 6 Leonard Isitt Drive, Auckland Airport, Auckland 2022 New Zealand; PH: 0800 787 865; email: [technical@rustoleum.co.nz](mailto:technical@rustoleum.co.nz), [www.rustoleum.co.nz](http://www.rustoleum.co.nz); **SOUTH AFRICA:** Rust-Oleum South Africa PTY. LTD. PO Box 400 Randvaal 1873 Gauteng, South Africa, PH: (016) 365 5120, email: [info@spraymate.co.za](mailto:info@spraymate.co.za), [www.rustoleum.co.za](http://www.rustoleum.co.za)

WATER-BASE  
LOW ODOUR

INTERIOR/EXTERIOR

WHITE  
(TINTABLE)

3.78 L



©2020 Rust-Oleum Corporation Made in the USA 362229 0120

362051 EXTREME ADHSN



0 20066 47956 5