



SHELLAC

TRADITIONAL FINISH AND SEALER

EASY TO APPLY

DRIES IN 1 HOUR

AMBER

OIL-BASED

INTERIOR

946 ml

Zinsser® Amber Shellac gives wood a rich, antique warmth with a lustrous mid-gloss finish that will not yellow or darken with age. Use Zinsser Amber Shellac to help seal out odours from pets, smoke and mildew.

RECOMMENDED FOR: Furniture, paneling and trim.

NOT RECOMMENDED FOR: Interior floors or exterior furniture.

SURFACE PREPARATION: Surface must be sound, dry and free of contaminants. Sand bare wood as smooth as possible. Stir well before using. Do not apply if humidity exceeds 80%. Not recommended for use as a sealer under polyurethane. **DO NOT THIN.**

APPLICATION: Apply one thin and even coat using a quality brush, pad or lint-free cloth and let dry 1 hour before sanding with 220 or finer grit sandpaper. Remove all dust and apply second coat. Allow any subsequent coats to dry at least 1 hour before sanding tightly and recoating. Two full coats will seal odours in porous surfaces. Apply one or two coats to knots and sap streaks to prevent bleeding into finish paint.

DRY TIME: Dries in 1 hour; recoats in 1 hour.

COVERAGE: Approx. 8 to 12 m² per 946 mL

DRY TIME: Dries in 30 minutes or less; recoat in 1 hour.

CLEAN UP: Clean wet tools and spills with denatured alcohol or household ammonia and water.

KEEP OUT OF REACH OF CHILDREN

FLAMMABLE

DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, sparks and open flames. - No smoking. Keep container tightly closed. Take precautionary measures against static discharge. Wear protective clothing and eye protection.

WARNING STATEMENTS: Highly flammable liquid and vapour. Causes serious eye irritation. May form explosive peroxides.

FIRST AID INSTRUCTIONS

IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Do NOT induce vomiting. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IN CASE OF FIRE:** Use alcohol resistant foam or normal protein foam for extinction. **IF ON SKIN (or hair):** Remove immediately all contaminated clothing. Rinse skin (or hair) with water.

STORAGE: Store in a well-ventilated place. Keep cool.

DISPOSAL: Dispose of contents/container in accordance with local regulations

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz.



RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 800 784 476
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

©2017 Rust-Oleum Corporation Made in USA 332500 1217

331308 AMBER SHELLAC



0 20066 38184 4