



TUNG OIL

PENETRATES & PROTECTS
ENHANCES NATURAL WOOD TONE
WILL NOT DARKEN WITH AGE

NATURAL

CAUTION
KEEP OUT OF REACH OF CHILDREN
FLAMMABLE
READ SAFETY DIRECTIONS
CONTAINS LIQUID HYDROCARBONS

OIL-BASED

INTERIOR

946 mL

CAUTION

KEEP OUT OF REACH OF CHILDREN

FLAMMABLE

DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, sparks and open flames. - No smoking. Avoid breathing vapours. Wear protective gloves, protective clothing and eye protection. Take precautionary measures against static discharge.

WARNING STATEMENTS: Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness and cracking.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Do NOT induce vomiting. Take off contaminated clothing and wash before reuse. **IN CASE OF FIRE:** Use alcohol resistant foam or normal protein foam for extinction. **IF ON SKIN (or hair):** Immediately remove all contaminated clothing. Rinse skin (or hair) with water. **IF INHALED:** Remove affected person to fresh air and keep at rest in a position comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned, seek medical attention.

STORAGE: Store in a well-ventilated place. Keep cool.

DISPOSAL: Rags, steel wool or waste soaked with Zinsser Tung Oil may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed water-filled metal container. For disposal of rags and unused amounts of product contact your local or state government environment control agency.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz

Zinsser® Tung Oil will quickly and easily restore and enhance the natural colour and warmth of wood in only a few simple steps. Tung Oil deeply penetrates into the surface of stained and unfinished wood to protect from moisture and provide the look of a genuine hand-rubbed finish. Zinsser's fast drying, ready-to-use formula will not darken over time and can be re-applied as needed to bring back the lustre and refresh the character of interior wood furniture, trim, moulding and more.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

RECOMMENDED USAGE: Interior wood substrates only.

NOT RECOMMENDED FOR: Floors or exterior surfaces.

APPLICATION: Use on dry wood from which all dirt, wax, grease and previous coatings have been removed so that Tung Oil can penetrate into the surface. Sand wood to an even, smooth finish and wipe clean. SHAKE CONTAINER THOROUGHLY and test for product compatibility on hidden section of wood. Using a brush or a lint-free cloth, apply a generous amount of Tung Oil in the same direction of the wood grain. Apply additional finish to areas that absorb all of the liquid. Keep the surface wet for 15 minutes to allow Tung Oil to penetrate into the wood then buff the surface with a clean, lint-free cloth. DO NOT THIN.

RECOAT: After 24 hours of dry time, apply a second coat and allow to penetrate the surface for 5-10 minutes before buffing with a clean, lint-free cloth. Two light coats are recommended for best appearance. Gloss level will increase with additional coats.

DRY TIME: Allow wood to completely dry for 24 hours before using.

MAINTENANCE: Periodically re-apply additional coats to refresh and enhance the gloss and surface of the wood as needed.

CLEAN UP: Clean application tools and equipment with mineral turps or paint thinner.

COVERAGE: 14 to 19 m² per 946 mL.

NOTE: Dry time varies with temperature, humidity and ventilation.

331309 TUNG OIL



0 20066 38185 1

RUST-OLEUM
CORPORATION

RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

©2017 Rust-Oleum Corporation Made in USA L331309R 1217

L331309R