



CLEAR VARNISH

SUPERIOR SCRATCH RESISTANCE

MAXIMUM DURABILITY

FAST DRY TIME

CLEAR
SATIN

CAUTION
KEEP OUT OF REACH OF CHILDREN
FLAMMABLE
READ SAFETY DIRECTIONS
CONTAINS LIQUID HYDROCARBONS

OIL-BASED

INTERIOR

3.78L

Zinsser® Clear Varnish is a protective top coat that has been specially formulated to provide the best protection against scratches and stains. Zinsser Clear Varnish leaves no brush marks and adds a warm, golden glow to your projects.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

RECOMMENDED FOR: Furniture, trim, cabinets, wood doors and panelling.

NOT RECOMMENDED FOR: Exterior surfaces, linoleum, vinyl or glazed tiles and metal. For wood floors, use Zinsser® Ultra Thick Floor Finish.

PREVIOUSLY FINISHED SURFACES: For best adhesion, surfaces must be clean, dry, and free of old finishes, dust, dirt, oils or other foreign matter. Old finishes, in poor condition must be removed. Sand to obtain a smooth surface. Do not use steel wool as rust may develop after finish has been applied. Remove all sanding dust using a vacuum or cloth dampened with mineral turps.

STAINED OR PAINTED WOOD: Follow manufacturer's direction for application of stain or paint. Make certain surface is thoroughly dry before applying Zinsser Clear Varnish. Refer to manufacturer's label for dry times. For best results, use a Zinsser® Wood Stain.

UNFINISHED SURFACE PREPARATION: Sand using 150-220 grit sandpaper and remove all sanding dust using a rag lightly dampened with mineral turps, or vacuum. If a filler or putty is used, make sure that it does not contain wax and allow for enough time to dry thoroughly.

APPLICATION TIPS: Use adequate ventilation at all times. Apply at temperatures above 13°C and below 32°C. Slower dry times may result from applications on redwood, cedar or woods with high oil content, use of stain or sealer, or periods of high humidity and/or low temperatures. To prevent bubbles in the finish, do not over-brush, shake container or apply with a roller. Zinsser Clear Varnish has a slight amber cast. Test Zinsser Clear Varnish in an inconspicuous area. Testing is particularly important when applying over paints or stains as the appearance of these products may change slightly when an oil-based finish is applied.

APPLICATION: Stir thoroughly before and during use. To prevent bubbles in the finish, DO NOT SHAKE CONTAINER. Apply using a good quality, synthetic bristle brush, foam brush or applicator. Allow finish to dry 8 hours and then re-coat. Lower temperatures and/or higher humidity may cause slower dry

times. Re-coat only when previous coats have dried clear and feel hard. (No longer feels tacky to the touch.) If any coat has dried more than 12 hours, lightly sand before re-coating.

DRY TIME: A minimum of 3 coats is recommended. Allow finish to dry 24 hours before light use. Wait 3 days before subjecting surface to normal usage.

CLEAN-UP: For easy clean-up, use paint thinner or mineral turps.

COVERAGE: 27 to 53 m² per 3.78 L

CAUTION

KEEP OUT OF REACH OF CHILDREN

FLAMMABLE

DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Do not breathe vapours. Use personal protective equipment as required. Avoid release to the environment.

WARNING STATEMENT May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

FIRST AID INSTRUCTIONS

Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IN CASE OF FIRE: Use alcohol resistant foam or normal protein foam for extinction. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. IF INHALED: Remove affected person to fresh air and keep at rest in a position comfortable for breathing.

STORAGE: Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL: Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz

RUST-OLEUM
CORPORATION

©2017 Rust-Oleum Corporation Made in USA 332584 1217

RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

331401 SATIN CLEAR VARNISH

