



WOOD GRAIN ENHANCER

ACCENTS WOOD GRAIN

BEFORE | AFTER

SHOWN ON
BLACK CHERRY STAIN

SHOWN ON
BLACK STAIN

CREATES
WHITE
GRAIN

WATER-BASED

INTERIOR

946 ml

Zinsser® Wood Grain Enhancer accents the wood grain on bare or stained wood. Create a colour contrast on a variety of projects. This product works best on wood with a significant grain pattern such as red oak, white oak or ash.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

RECOMMENDED FOR: Wood surfaces only.

NOT RECOMMENDED FOR: Floors and exterior surfaces.

PREPARATION: Start with bare wood. Use a clean rag dampened with water and wipe over wood. Lightly use a steel brush on the wood in the direction of the grain. Remove dust with a clean, dry rag. Allow surface to dry. **OPTIONAL:** Stain can be applied to add colour to wood. For best results use Zinsser® wood stains.

TESTING COLOUR: To verify the final look, test Zinsser Wood Grain Enhancer in an inconspicuous area.

APPLICATION: Stir material thoroughly before and occasionally during use. For best results use at temperature between 16°C and 32°C. Apply Wood Grain Enhancer liberally to wood with a lint-free rag against the grain. With a clean rag, wipe against the wood grain to wipe away excess material. Wood Grain Enhancer will sit in the grain and create your final look.

PROTECTING THE FINAL FINISH: To complete your project and for the best protection, finish with any clear Zinsser® varnish depending on your project needs. A clear Zinsser varnish can be applied 2 hours after application of the Wood Grain Enhancer.

COVERAGE: Up to 14 m² per 946 mL.

CLEAN UP: Soap and water.

DO NOT THIN.

CAUTION

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Use personal protective equipment as required.

WARNING STATEMENT: May cause damage to fertility or the unborn child if prolonged exposure occurs.

FIRST AID INSTRUCTIONS

IF exposed or concerned: Get medical advice.

STORAGE: Store locked up.

DISPOSAL: Dispose of contents/container in accordance with local regulations.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz.



RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 478
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

©2017 Rust-Oleum Corporation Made in USA 332596 1217

331561 WHITE GRAIN



0 20066 38251 3