



Zinsser® Stain & Varnish is the ultimate convenience product for staining and finishing. This revolutionary water-based formula allows out apply both stain and varnish in one easy step with the ease of soap and water leaen-up. Fast drying and virtually odouries, the combination of wood stain and varnish into one product allows projects to be finished quickly. Achieve a deep, rich colour from premium pigements and protect with a durable semi-gloss finish. Highlight wood's beauty on furniture, cabinets and more using Zinsser Stain & Varnish.

READ ALL DIRECTIONS REFORE REGINNING PROJECT

RECOMMENDED FOR: Interior wood furniture, trim, cabinets and doors.

NOT RECOMMENDED FOR: Floors or exterior surfaces.

SURFACE PREPARATION: Remove any existing finishes with sandpaper or stripper. Prepare bare wood for staining by sanding in the direction of the grain. Begin with 150 grit sandpaper and progress through 180 and 220 grits. Before using product, remove all sanding dust, dirt, grease or glue with a vaccium, or clean rag dampened with mineral turps.

TESTING COLOUR: Be sure to test Zinsser Stain & Varnish to verify the desired colour. To test, apply in an inconspicuous area. For a deeper colour, additional coats may be applied.

APPLICATION: Stir the contents thoroughly before use. DO NOT SHAKE CONTAINER, Apply with a high-quality, synthetic bristle brush in the direction of the grain. Apply in a thin coat until a uniform film has been achieved. To prevent brush marks, avoid excessive brushing. Some in raise may occur. If so, lightly sand surface using 220 grit sandpaper. Wipe off sanding dust. Apply second coat. One coat application is recommended. If desired, additional coats can be applied with one hour dry time between coats.

COVERAGE: Up to 2 m². Coverage may vary depending on the applicator or wood species used.

CLEAN UP: For fast, easy clean-up, use soap and water.

STORAGE: Store in a dry, well-ventilated place. Keep from freezing.

DISPOSAL: If spilled, contain spilled material and remove with inert absorbent. Dispose of

RUST-OLEUM

©2018 Rust-Oleum Corporation Made in USA L335802R 0118

RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH. 1 300 784 476
Www.msbloeum.com.au
www.msbloeum.com.au
www.msbloeum.com.au

sales@rustoleum.com.au

contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

KEEP OUT OF REACH OF CHILDREN DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Read label before use. Keep away from heat, sparks and farme – No Smoking, would breathing immes, vapours, or mist. Ensure fresh air entry during application and dyring. If you experience eye watering, headache or dizziness, wear an appropriate, properly fitted respirator during and after application. Wash throughly wither handling. And contact with eyes, skin and clothing.

WARNING STATEMENTS: May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye irritation. Harmful if swallowed. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

FIRST AID INSTRUCTIONS

Info@havdn.co.nz

IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Do NOT induce vorniling. If ON SKIN for hard immediately remove all contaminated oftning. Rinse skin for hard with water. Wash contaminated oftning before reuse. Absorb spillage to prevent material damage. If IN EYES, Rinse cautiously with water for several minutes a Remove contact lenses, if present and easy to 60. Confluen insign. IF IN EYED. Remove affected person to refind and keep at reit in a position comfortable for breathing. IN CASE OF FIRE: Use alcohol resistant foam or fine spray/water for or extinction.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz

335802 DARK WALNUT



AUS Zinsser Stain&Varn 237.indd 5 2/2/18 11:29 AM