



BAMBOO OIL

DEEP PENETRATING FORMULA

UV PROTECTION, WATER REPELLENT

SUPERIOR DIRT & MOULD PROTECTION

LONGER LASTING FINISH

NATURAL
GLOSS

WATER-BASED

EXTERIOR

4L

Zinsser® Bamboo Oil is a water-based exterior top coat sealer designed specifically for bamboo surfaces. The best way to maintain the condition and lengthen the life of bamboo is to seal it and Zinsser's Bamboo Oil delivers the ultimate protection for your bamboo. Zinsser Bamboo Oil is easy to apply, self-priming and protects against the sun's harsh UV rays. Zinsser Bamboo Oil dries to an enhanced gloss transparent finish.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

RECOMMENDED FOR: Exterior bamboo surfaces, both horizontal and vertical. Also great for use on screen fences, gates, cladding and exterior doors and furniture.

NOT RECOMMENDED FOR: Interior floors.

APPLICATION TIPS: For best results, apply in temperatures between 23°C and 27°C. Do not apply if humidity is greater than 85% or temperature is below 5°C.

SURFACE PREPARATION: The performance of Zinsser Bamboo Oil depends on the quality of the surface preparation. Do not apply Zinsser Bamboo Oil on wet bamboo as this may cause film defects, such as loss of adhesion and uneven pigmentation.

NEW BAMBOO SURFACES: All grease, oil, grime, sap, and other contaminants must be removed with a cleaning solution, such as Zinsser® Deck Bright, using a soft bristle broom or brush.

PREVIOUSLY COATED BAMBOO: Remove all solvent based and water-based oils by applying Zinsser® Timber Clean using a stiff bristle broom to scrub the surface and leave on for 5 minutes. Remove with clean water. Use 320 grit sandpaper to sand back painted surfaces to a raw bamboo, or apply Zinsser® Gel Stripper and scour to remove stains, acrylic, polyurethanes etc. Followed by washing with Zinsser® Timber Prep to neutralise the surface (this is very important).

APPLICATION: Make sure bamboo is dry and free of moisture, we recommend applying after bamboo has been exposed to dry weather for a minimum of 3 to 5 days. Apply a thin coat of Zinsser Bamboo Oil onto the bamboo using an industrial coating brush, paint brush, pressure washer (using a fine tip with 1800 PSI) or lint free cloth. Wipe off all excess material with the brush or rag and allow 1-2 hours for curing depending on the weather conditions. For best results, apply 2 coats for bamboo screening and 3 coats for outdoor bamboo furniture Note: Colour will deepen with the number of coats applied.

RECOAT TIME: Allow 1-2 hours dry time between coats.

DRY TIME: Dries to the touch in 10-15 minutes with good ventilation. Zinsser Bamboo Oil will fully cure in 2 hours. Note: Dry times will be slower in cold, damp conditions or if applied in high humidity

COVERAGE: Up to 20m² per litre.

CLEAN UP: Use soap and water for clean-up.

STORAGE: Store in a cool, dry place.

CAUTION

KEEP OUT OF REACH OF CHILDREN

DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Use personal protective equipment as required. Apply in a well-ventilated area.

WARNING STATEMENTS: May cause skin or eye irritation.

FIRST AID INSTRUCTIONS

IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Do NOT induce vomiting. **IF IN EYES/ ON SKIN:** Immediately flush skin and eyes with soap and water. IF exposed or concerned: Get medical advice.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz.

 **RUST-OLEUM**
CORPORATION

©2017 Rust-Oleum Corporation Made in Australia 1217

RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
Info@haydn.co.nz

335941 NATURAL

