



TIMBER & DECKING FINISH



TRANSPARENT, NATURAL FINISH

REJUVENATES AND RESTORES

PROTECTS AGAINST HARSH
WEATHER CONDITIONS

BEFORE

AFTER

JARRAH
MATT

WATER-BASED

EXTERIOR

4L

Zinsser® Timber & Decking Finish is a long lasting water-based timber finish made from superior ingredients and pigments. The penetrating formula is designed to coat and protect the timber from the harsh conditions. It produces a transparent natural, matt finish leaving the timber looking new and natural. Zinsser Timber & Decking Finish also rejuvenates previously coated, stained or oiled timber bringing back its natural beauty.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

RECOMMENDED FOR: Exterior and interior timber including decks, pergolas, walkways, hand rails, fences, furniture, wall cladding, doors, windows and rough sawn timber.

NOT RECOMMENDED FOR: Interior floors

APPLICATION TIPS: Ensure that Zinsser Timber & Decking Finish is rubbed into the timber grain and is not allowed to sit on the surface as this will affect the longevity of the finish. Use a water-based filler/putty on any timber to fill holes and imperfections. Sand smooth and dust clean.

SURFACE PREPARATION: Do not apply Zinsser Timber & Decking Finish if rain or night moisture is imminent within 2 hours of application. Zinsser Timber & Decking Finish can only be applied to raw timber. All other oils or coatings, including lacquers and stains, must be thoroughly stripped clean or sanded down to raw timber.

NEW TIMBER COATING: Remove all grease, oil, grime, sap, tannins and other contaminants using Zinsser® Timber Clean and wash with Zinsser® Timber Prep to neutralise and open the surface (this is very important).

PREVIOUSLY PAINTED TIMBER: Painted or oiled surfaces should be sanded back to raw timber using 40-80 grit sand paper before applying Zinsser Timber & Decking Finish. Alternatively, apply Zinsser® Deck Stripper by scouring to remove stains, acrylic, polyurethanes and decking oils, followed by washing with Zinsser® Timber Prep.

OLD WEATHERED TIMBER: Remove surface growth, moss, lichen and mould, by mixing 1 part household bleach to 8 parts water and apply to a wetted deck using a stiff scrubbing brush. Wait 10 minutes and thoroughly rinse with fresh water. After all sanding and stripping has been completed and prior to application of Zinsser Timber & Decking Finish, clean and neutralise the surface with Zinsser® Timber Prep. Thoroughly rinse the surface and allow 24 hours for the timber to dry.

APPLICATION: Apply Zinsser Timber & Decking Finish to 2-3 boards at a time using a lamb's wool applicator, brush or rag, rubbing thoroughly into the grain of the timber to achieve good penetration. Allow for an even coating and wipe off all excess material with the applicator or brush. Repeat this process until all boards have been coated. Always maintain a wet edge. Allow 1-2 hours for curing depending on the weather conditions. Do NOT apply Zinsser Timber & Decking Finish on wet timber as this may result in film defects such as loss of adhesion and uneven pigmentation.

RECOAT: Additional coats may be applied as above ensuring Zinsser Timber & Decking Finish is evenly rubbed into the timber. For best results, 3 coats are recommended.

DRY TIME: Decking can be walked on once the surface dries, about 1 hour. Allow 2-3 hours dry time before furniture is put on the surface.

CLEAN UP: Clean up with cold water.

COVERAGE: Up to 20m² per litre, depending on surface texture and porosity of the timber.

MAINTENANCE: Zinsser Timber & Decking Finish will give a long life and it is recommended that a regular inspection of the surface should be done every 12/18 months, if the surface is showing signs of deterioration, reduced colour or luster; it is recommended that a fresh coat be applied to maintain full protection of the timber. Wash the timber surface with Zinsser® Deck Bright and apply 1-2 coats of Zinsser Timber & Decking Finish to rejuvenate the coating.

CAUTION

KEEP OUT OF REACH OF CHILDREN

DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Use personal protective equipment as required. Apply in a well-ventilated area.

WARNING STATEMENTS: May cause skin or eye irritation.

FIRST AID INSTRUCTIONS

IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Do NOT induce vomiting. **IF IN EYES/ ON SKIN:** Immediately flush skin and eyes with soap and water. IF exposed or concerned: Get medical advice.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz.

 **RUST-OLEUM**
CORPORATION

©2017 Rust-Oleum Corporation Made in Australia 1217

RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

335935 JARRAH MATT



0 20066 42048 2