



## EXTERIOR VARNISH

**SUPERIOR UV PROTECTION**  
**MOULD & MILDEW RESISTANT**  
**SEALS OUT WATER**

**CAUTION**  
KEEP OUT OF REACH OF CHILDREN  
FLAMMABLE  
READ SAFETY DIRECTIONS  
CONTAINS LIQUID HYDROCARBONS

**CLEAR  
GLOSS**

OIL-BASED

EXTERIOR

473 ml

**Zinsser® Exterior Varnish** is the best solution to protect exterior wood against extreme weather conditions. It is specially formulated to provide superior durability and flexible enough to expand and contract as the wood and weather changes. UV inhibitors reduce fading and superior mould and mildew resistance makes your outdoor projects last for years. Zinsser Exterior Varnish is fast drying and provides a warm golden glow.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

**RECOMMENDED FOR:** Exterior wood surfaces. Ideal for: railings, fences, patio furniture, house trim, boats (above the waterline).

**NOT RECOMMENDED FOR:** Decks or high traffic areas, cladding or rough-sawn surfaces.

**PREVIOUSLY FINISHED SURFACES:** For best adhesion, surfaces must be clean, dry and free of wax, grease, oil, shellac, lacquer, mildew and polishes. Remove wax with a wax stripper, shellac with a paint stripper, and mildew with a solution of up to 10% household bleach and tap water. Old finishes in poor condition must be removed. Sand to obtain a smooth surface. Remove all sanding dust using a vacuum or cloth dampened with mineral turps.

**STAINED OR PAINTED WOOD:** Follow manufacturer's direction for application of stain or paint. Make certain surface is thoroughly dry before applying Zinsser Exterior Varnish. Refer to manufacturer's label for dry times.

**UNFINISHED SURFACE PREPARATION:** Sand smooth using 120-150 grit sandpaper and remove all sanding dust. If a filler or putty is used, make sure that it does not contain wax and allow enough time for it to dry thoroughly.

**APPLICATION TIPS:** Use adequate ventilation at all times. Do not apply in direct sunlight. Apply at temperatures above 13°C and below 32°C. Slower dry times may result from applications on hard exotic woods, use of stain or sealer, or periods of high humidity and/or low temperatures. Use care when applying over white or pastel paints or stains as discolouration may occur. Do not dilute. Test Zinsser Exterior Varnish in an inconspicuous area before beginning. Testing is particularly important when applying over paints or stains as the appearance of these products may change slightly when an oil-based finish is applied.

**APPLICATION:** Stir thoroughly before and during use. Apply using a good quality, natural bristle brush, or applicator. To prevent bubbles in the finish, do not over-brush, shake container or apply with a roller. Allow finish to dry 4 hours and then re-coat. Lower temperatures and/or higher humidity may cause slower dry times. Re-coat only when previous coats have dried clear and feel hard. (Should no longer feel tacky to the touch.) If the coat has dried more than 12 hours, lightly sand before re-coating. A minimum of 3 coats is recommended. Allow finish to dry 24 hours before light use. Wait 3 days before subjecting surface to normal usage.

**CLEAN UP:** For easy clean-up, use paint thinner or mineral turps.

**COVERAGE:** 7 to 8 m<sup>2</sup> per 473 mL

**RUST-OLEUM**  
CORPORATION

**RUST-OLEUM AUSTRALIA PTY. LTD.**  
Unit 12, 4 Southridge Street  
Eastern Creek, NSW 2766 Australia  
PH: 1 300 784 476  
www.rustoleum.com.au  
sales@rustoleum.com.au

**HAYDN BRUSH CO. LTD.**  
PO Box 86054  
Christchurch 7675 NZ  
PH: 64 3 347 7770  
www.rustoleum.co.nz  
info@haydn.co.nz

### CAUTION

**KEEP OUT OF REACH OF CHILDREN**

**FLAMMABLE**

**DO NOT SWALLOW**

**CONTAINS: Liquid Hydrocarbons and 3-Iodo-2-Propynyl Butyl Carbamate - 0.03 g/L**

**SAFETY DIRECTIONS:** If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, sparks and open flames. - No smoking. Do not breathe vapours. Use personal protective equipment as required. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Avoid release to the environment.

**WARNING STATEMENTS** Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Suspected of causing cancer. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness and cracking.

### FIRST AID INSTRUCTIONS

If exposed or concerned: Get medical advice. IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Do NOT induce vomiting. Take off contaminated clothing and wash before reuse. IN CASE OF FIRE: Use alcohol resistant foam or normal protein foam for extinction. IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin (or hair) with water. IF INHALED: Remove affected person to fresh air and keep at rest in a position comfortable for breathing.

**STORAGE:** Store in a well-ventilated place. Keep cool.

For further information refer to the Safety Data Sheet available at [www.rustoleum.com.au](http://www.rustoleum.com.au) or [www.rustoleum.co.nz](http://www.rustoleum.co.nz)

**331332 GLOSS EXTERIOR VARNISH**



9700314863

0118