



# TIMBER SEALER

WORKS WITH OIL OR WATER-BASED FINISHES

SEALS WOOD GRAIN

EASY TO SAND

CAUTION  
KEEP OUT OF REACH OF CHILDREN  
DO NOT SWALLOW  
READ SAFETY DIRECTIONS

WATER-BASED

INTERIOR

946 ml

**Zinsser® Timber Sealer** is a fast drying sealer that prepares timber surfaces to be top coated. Zinsser Timber Sealer reduces the tendency for lighter coloured timbers to darken once they are top coated. Zinsser Timber Sealer dries clear, is virtually odourless and provides for soap and water clean up.

REAL ALL DIRECTIONS BEFORE BEGINNING PROJECT.

**RECOMMENDED FOR:** As a base finish coat on interior bare or stained wood surfaces. Ideal for: Furniture, trim, cabinets, doors, and paneling.

**NOT RECOMMENDED FOR:** Exterior surfaces, Linoleum, vinyl or glazed tiles, and metal.

**PREVIOUSLY FINISHED SURFACES:** For best adhesion, surfaces must be clean, dry and free of old finishes, dust, dirt, oils or other foreign matter. Old finishes in poor condition must be removed. Sand to obtain a smooth surface. Do not use steel wool as rust may develop after finish has been applied. Remove all sanding dust using a vacuum or cloth dampened with mineral turps.

**STAINED WOOD:** Apply stain prior to applying Zinsser Timber Sealer. Follow manufacturer's direction for application of stain. Allow stain to thoroughly dry before applying Zinsser Timber Sealer. Refer to stain manufacturer's label for dry times.

**UNFINISHED SURFACE PREPARATION:** Sand wood with 180 grit sandpaper and remove all sanding dust using a rag lightly dampened with mineral turps, or vacuum. If a filler or putty is used, make sure that it does not contain wax and allow for enough time to dry thoroughly.

**APPLICATION TIPS:** Product appears milky when wet but dries to a clear coating. After extended periods of sitting, the product may appear to have separated. This is normal and can be easily stirred back together. Use adequate ventilation at all times. Do not apply in direct sunlight. Apply at temperatures above 13°C to 32°C. Use care when applying over white or pastel paints and stains as discolouration may occur. Test Zinsser Timber Sealer in an inconspicuous

area before beginning. To prevent bubbles in the finish do not over-brush, shake container or apply with a roller.

**APPLICATION:** Stir thoroughly before and during use. To prevent bubbles in the finish, DO NOT SHAKE CONTAINER. Apply using a good quality, synthetic bristle brush, foam brush or applicator. Allow finish to dry 2 hours. Lower temperatures and/or higher humidity may cause slower dry times. Lightly sand Timber Sealer with 220-280 grit sandpaper. A powder should develop when sanded. Do not over-sand or the product will be totally removed, or the stain may be removed. Remove the sanding dust with a clean rag or vacuum. Apply the wood finish of your choice. For best results, use any clear Zinsser® varnish. Follow manufacturer's directions. Allow finish to dry 24 hours before light use. Wait 3 days before subjecting surface to normal usage.

**CLEAN UP:** For fast, easy clean-up, use soap and water.

**COVERAGE:** 5 to 8 m<sup>2</sup> per 946 mL

**CAUTION**

**KEEP OUT OF REACH OF CHILDREN**

**SAFETY DIRECTIONS:** If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Use personal protective equipment as required.

**WARNING STATEMENT:** May damage fertility or the unborn child if prolonged exposure occurs

**FIRST AID INSTRUCTIONS**

If exposed or concerned: Get medical advice.

**STORAGE:** Store locked up

**DISPOSAL:** Dispose of contents/container in accordance with local regulations.

For further information refer to the Safety Data Sheet available at [www.rustoleum.com.au](http://www.rustoleum.com.au) or [www.rustoleum.co.nz](http://www.rustoleum.co.nz).




**RUST-OLEUM AUSTRALIA PTY. LTD.**  
Unit 12, 4 Southridge Street  
Eastern Creek, NSW 2766 Australia  
PH: 1 300 784 476  
[www.rustoleum.com.au](http://www.rustoleum.com.au)  
[sales@rustoleum.com.au](mailto:sales@rustoleum.com.au)

**HAYDN BRUSH CO. LTD.**  
PO Box 86054  
Christchurch 7675 NZ  
PH: 64 3 347 7770  
[www.rustoleum.co.nz](http://www.rustoleum.co.nz)  
[info@haydn.co.nz](mailto:info@haydn.co.nz)

©2017 Rust-Oleum Corporation Made in USA 332702 1217

331375 TIMBER SEALER



0 20066 38219 3

332702 1217