

CAUTION

KEEP OUT OF REACH OF CHILDREN
DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing vapours. Keep away from heat, sparks and open flames. - No smoking. Wear protective gloves/clothing.

WARNING STATEMENTS: Combustible liquid. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness and cracking.

FIRST AID INSTRUCTIONS

IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Rinse mouth. Do NOT induce vomiting. **IN CASE OF FIRE:** Use alcohol resistant foam or normal protein foam for extinction. **IF ON SKIN:** Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. **IF INHALED:** Remove affected person to fresh air and keep at rest in a position comfortable for breathing.

STORAGE: Store in a well-ventilated place. Keep cool.

DISPOSAL: Dispose of contents/container in accordance with local regulations.

For further information refer to the Safety Data Sheet available at
www.rustoleum.com.au or
www.rustoleum.co.nz

Zinsser® Satin Wax is a liquid solvent-based wax that leaves a beautifully rich, soft satin sheen while providing an additional level of protection and water resistance to oil-finished or bare woods. Use Zinsser Satin Wax in Natural for light-coloured wood.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

RECOMMENDED FOR: Furniture, trim, panelling or any interior bare or oil-finished wood surface.

NOT RECOMMENDED FOR: Floors or exterior surfaces.

APPLICATION: Allow any previously applied oil or stain on wood surface to dry 72 hours before applying Zinsser Satin Wax. MIX CONTAINER THOROUGHLY. Spread a thin, even coat of Zinsser Satin Wax with a clean lint free cloth. Wait 10 minutes, wipe clean and dry. Polish with a soft cloth.

MAINTENANCE: Periodically apply additional coats of Zinsser Satin Wax as needed, buffing with a soft cloth. For additional sheen, reapply Zinsser Satin Wax and wet sand surface lightly with 600-grit stearate-free wet/dry sandpaper, sanding in the direction of the wood grain. After 10 minutes wipe clean and dry, then polish with a soft cloth.

CLEAN UP: For fast, easy clean-up, use paint thinner or mineral turps.

NOTE: Do not apply surface finishes, such as varnish, over wax. If a clear wood finish (such as varnish) is desired, completely remove wax with a wax stripper, following product directions, and allow wood surface to dry for 72 hours before applying Zinsser® Clear Varnish.



RUST-OLEUM AUSTRALIA PTY. LTD. **HAYDN BRUSH CO. LTD.**
Unit 12, 4 Southridge Street PO Box 86054
Eastern Creek, NSW 2766 Australia Christchurch 7675 NZ
PH: 1 300 784 476 PH: 64 3 347 7770
www.rustoleum.com.au www.rustoleum.co.nz
sales@rustoleum.com.au info@haydn.co.nz

©2017 Rust-Oleum Corporation Made in USA 331853 1217

331415 NATURAL SATIN WAX



0 20066 38190 5