



WEATHERED WOOD ACCELERATOR

CREATES A WEATHERED LOOK

BEFORE | AFTER

SHOWN ON
RED OAK WOOD

SHOWN ON
PINE WOOD

AGED
LOOK IN
MINUTES

WATER-BASED

INTERIOR

946 ml

Zinsser® Weathered Wood Accelerator creates a weathered look on bare or untreated wood. It replicates the ageing process that happens in nature by reacting with the tannins of the wood to create a unique one-of-a-kind aged grey look. It works on all types of wood. Final look will vary on wood type. This water-based formula is low odour.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

RECOMMENDED FOR: Wood surfaces only.

NOT RECOMMENDED FOR: Floors and exterior surfaces.

PREPARATION: Remove any existing finishes with sandpaper or liquid stripper. Weathered Wood Accelerator works best on bare or untreated wood. Prepare bare wood for the Weathered Wood Accelerator by sanding in the direction of the grain with a 100 grit sandpaper. Finish can also be applied on reclaimed wood.

TESTING COLOUR: Weathered Wood Accelerator reacts differently with different types of wood. To verify the final look, test Weathered Wood Accelerator in an inconspicuous area.

APPLICATION: Stir or shake material thoroughly before and occasionally during use. For best results, use at temperature between 16°C and 32°C. Apply with a synthetic bristle brush or foam brush. Allow Weathered Wood Accelerator to sit on wood for 30 minutes to 1 hour for the final effect (wiping away is not

required). For a lighter effect, apply product and wipe away immediately or lightly sand finish with fine grit sandpaper once dry. To darken, a second coat can be applied after 1 hour. If you want to remove the Weathered Wood Accelerator, apply bleach to the surface, and wipe off.

PROTECTING THE FINAL FINISH: For the best protection you can apply a top coat. Wait 2 hours for Weathered Wood Accelerator to dry. For interior surfaces such as furniture and cabinetry, you can top coat with a Lacquer spray. If you choose to top coat with a varnish, seal with a lacquer spray and then apply Zinsser® Clear Varnish. Test in an inconspicuous area first. Some top coats may continue to react with the Weathered Wood Accelerator affecting the final look.

COVERAGE: Up to 25.5 m² per 946 mL.

CLEAN UP: Soap and water.

CAUTION

KEEP OUT OF REACH OF CHILDREN.

DO NOT SWALLOW.

FIRST AID INSTRUCTIONS

IF IN EYES/ ON SKIN: Immediately flush skin and eyes with soap and water. IF exposed or concerned: Get medical advice.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz.



RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

©2017 Rust-Oleum Corporation Made in USA 332594 1217

331421 WEATHERED WOOD



0 20066 38255 1

Plastic Qt 332594