

Zinsser<sup>®</sup> Floor Finish provides the ultimate protection for your wood floors. Zinsser Floor Finish is formulated with patented Aluminium Oxide Nano Technology to provide the best scuff and scratch protection available, as proven by independent lab testing. It or woods with a high oil content, use of stain or sealer, or periods of high humidity s ideal for high traffic areas, and stands up to years of abuse. From children's toys pet scratches, nothing gives you better protection for your wood floors. More than twice as durable as traditional wood finishes, Zinsser Floor Finish in an inconspicuous area before beginning. Testing is particularly important when applying over paints or provides a warm golden glow to your floors and dries faster than most oil-based floor products. 1.375" Holes

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

.187" copy margin

RECOMMENDED USAGE: Interior bare wood or stained floors.

NOT RECOMMENDED FOR: Exterior surfaces, Linoleum, vinyl or glazed tiles and metal.

PREVIOUSLY FINISHED SURFACES: For best adhesion, surfaces must be clean, dry and free of wax, grease, oil, shellac, lacquer, mildew and polishes. Waxes must be removed with a wax stripper; sanding does not remove wax. Shellac must be removed with a paint stripper. Previously finished floors in good condition should be cleaned with a T.S.P. (Tri Sodium Phosphate) solution in water, and rinsed thoroughly with clean water. Do not use T.S.P. on bare wood floors as discolouring will occur. Some types of prefinished or factory finished floors may not be compatible with Zinsser Floor Finish. Old finishes in poor condition must be removed. Use a floor sander to obtain a smooth surface. Remove all sanding dust using a vacuum or cloth dampened with mineral turps. Warning: Sanding dust can be a spontaneous combustion hazard. Always dispose of collected sanding dust immediately.

STAINED OR PAINTED WOOD: Follow manufacturer's directions for application of stain or paint. Make certain surface is thoroughly dry before applying Zinsser Floor Finish. Refer to manufacturer's label for dry times. For best results, use Zinsser<sup>®</sup> Wood Stains.

APPLICATION: Stir thoroughly before and during use. To prevent bubbles in the finish, DO NOT SHAKE CONTAINER. Apply using a good quality, natural bristle brush or wool applicator.

**RECOAT:** Allow finish to dry a minimum of 12 hours and then re-coat. Lower temperatures and/or higher humidity may cause slower dry times. Re-coat only when previous coats have dried clear and feel hard (no longer tacky to the touch). Lightly sand before re-coating. Apply additional coats following directions above. A total of 3 coats is recommended.

DRY TIME: Allow finish to dry 24 hours before light use. Wait 3 days before subjecting surface to normal usage.

UNFINISHED SURFACE PREPARATION: Use a sander to sand the new wood surface. Remove dust with a rag dampened with mineral turps, or with a vacuum.



©2017 Rust-Oleum Corporation Made in USA 332701 1217

RUST-OLEUM AUSTRALIA PTY. LTD. HAYDN BRUSH CO. LTD. Unit 12, 4 Southridge Street Eastern Creek, NSW 2766 Australia PH: 1 300 784 476 www.rustoleum.com.au sales@rustoleum.com.a

PO Box 86054 Christchurch 7675 NZ PH: 64 3 347 7770 www.rustoleum.co.nz info@haydn.co.nz



stains as the appearance of these products may change when an oil-based finish is applied. CLEAN-UP: For easy project clean-up, use paint thinner or mineral turps. **COVERAGE:** 48 to 56 m<sup>2</sup> per 3.78 L CAUTION KEEP OUT OF REACH OF CHILDREN FLAMMABLE DO NOT SWALLOW SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, sparks and open flames. - No smoking. Do not breathe vapours. Use personal protective equipment as required. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Avoid release to the environment.

**APPLICATION TIPS:** Use adequate ventilation at all times. Apply at temperatures above

13°C and below 32°C. Slower dry times may result from applications on redwood, cedar

and/or low temperatures. Do not dilute. To prevent bubbles in the finish, do not

over-brush, shake or apply with a roller. Test Zinsser Floor Finish in an inconspicuous

WARNING STATEMENTS: Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness and cracking.

FIRST AID

IF exposed or concerned: Get medical advice. IF SWALLOWED: Immediately call a POISON CENTRE (Phone: AUS 13 11 26; NZ 0800 764 766) or doctor. Do NOT induce vomiting. Take off contaminated clothing and wash before reuse. IN CASE OF FIRE: Use alcohol resistant foam or normal protein foam for extinction. IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin (or hair) with water. IF INHALED: Remove affected person to fresh air and keep at rest in a position comfortable for breathing.

STORAGE: Store in a well-ventilated place. Keep cool.

DISPOSAL: Dispose of contents/container in accordance with local regulations.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz.