



FLOOR FINISH

ULTIMATE DURABILITY

MAXIMUM SCUFF AND
ABRASION RESISTANCE

HIGH
TRAFFIC
FORMULA

CLEAR
SEMI-GLOSS

WATER-BASED

INTERIOR

3.78L

Zinsser Floor Finish® provides the ultimate protection for your floors that is diamond hard, diamond clear, and diamond beautiful. Zinsser Floor Finish is formulated with patented Aluminium Oxide Nano Technology to provide the best scuff and scratch protection available, as proven by independent lab testing. It is ideal for high traffic areas, and stands up to years of abuse. Nothing gives you better protection for your wood floors. Over twice as durable as traditional wood finishes and extremely fast drying, Zinsser Floor Finish is crystal clear, virtually odourless and provides for easy, water clean-up.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

RECOMMENDED FOR: Interior bare wood or stained floors.

NOT RECOMMENDED FOR: Linoleum, vinyl or glazed tiles and metal.

PREVIOUSLY FINISHED SURFACES: For best adhesion, surfaces must be clean, dry and free of wax, grease, oil, shellac, lacquer, mildew and polishes. Waxes must be removed with a wax stripper; sanding does not remove wax. Shellac must be removed with a paint stripper. Previously finished floors in good condition should be cleaned with a T.S.P. (Tri Sodium Phosphate) solution in water, and rinsed thoroughly with clean water. Do not use T.S.P. on bare wood floors as discolouring will occur. Some types of prefinished or factory finished floors may not be compatible with Zinsser Floor Finish. Old finishes in poor condition must be removed. Use a floor sander to obtain a smooth surface. Do not use steel wool as rust may develop after the finish has been applied. Remove all sanding dust using a vacuum or cloth dampened with mineral spirits.

STAINED OR PAINTED WOOD: Follow manufacturer's direction for application of stain or paint. Make certain surface is thoroughly dry before applying Zinsser Floor Finish. Refer to manufacturer's label for dry times. For best results, use Zinsser® Wood Stains.

APPLICATION: Stir thoroughly before and during use. To prevent bubbles in the finish, DO NOT SHAKE CONTAINER. Apply using a good quality, synthetic bristle brush, foam brush or applicator.

RECOAT: Allow finish to dry a minimum of 2 hours and then re-coat. Lower temperatures and/or higher humidity may cause slower dry times. Re-coat only when previous coats have dried clear and feel hard. (A powder should develop when lightly sanded.)

DRY TIME: If any coat has dried more than 24 hours, lightly sand before re-coating. Apply additional coats following directions above. A minimum of 4 coats is recommended. If grain raise occurs, sand smooth before final coat. Allow finish to dry 24 hours before light use. Wait 3 days before subjecting surface to normal usage.

UNFINISHED SURFACE PREPARATION: Use a sander to sand the new wood surface. Remove dust with a rag dampened with mineral turps, or with a vacuum.

APPLICATION TIPS: Product appears milky when wet but dries to a crystal clear coating. Use adequate ventilation at all times. Do not apply in direct sunlight. Apply at temperatures above 12°C and below 38°C. Use care when applying over white or pastel paints or stains as discolouration may occur. To prevent bubbles in the finish, do not over-brush, shake container or apply with a roller. Test Zinsser Floor Finish in an inconspicuous area before beginning. Testing is particularly important when applying over paints or stains as the appearance of these products may change when a water-based finish is applied.

CLEAN-UP: For fast, easy clean-up use water.

COVERAGE: 37 to 46 m² per 3.78L

CAUTION

KEEP OUT OF REACH OF CHILDREN

DO NOT SWALLOW

SAFETY DIRECTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Use personal protective equipment as required.

WARNING STATEMENTS: May damage fertility or the unborn child if prolonged exposure occurs.

FIRST AID INSTRUCTIONS

IF exposed or concerned: Call a physician.

STORAGE: Store locked up. Keep from freezing.

DISPOSAL: Dispose of contents/container in accordance with local regulations.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz

RUST-OLEUM
CORPORATION

©2017 Rust-Oleum Corporation Made in USA 9700314873 1217

RUST-OLEUM AUSTRALIA PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch 7675 NZ
PH: 64 3 347 7770
www.rustoleum.co.nz
info@haydn.co.nz

331382 SEMI-GLOSS FLOOR FINISH

