

HiChem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 563

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.auwww: hichem.com.au**Emergency****Poisons Information Centre 13 11 26****Contact****HiChem****HiChem Paint Technologies**
(03) 9796 3400 8am-4pm**Product Use:** HICHEM Thinner T 306 is use as a retarder thinner for industrial products.**HAZARD IDENTIFICATION**The product is classified as **Dangerous Goods** and **Hazardous Substance** in accordance to SAFE WORK AUSTRALIA {HSIS} and GLOBALLY HARMONISED SYSTEM {GHS} criteria.**GHS requirements.**

Classification of the substance or mixture

Flammable liquids – (Category 3)

Carcinogenic – (Category 2)

Mutagenic – (Category 1B)

Dermal, Inhalation and Eye Irritation – (Category 2)

Acute Toxicity – inhalation dermal, oral (Category 3)

Environment – Aquatic Organisms

DANGER**Hazard Statements**

H226: Flammable liquid and vapour

H302/312/332: Harmful if swallowed, in contact with skin and if inhaled.

H304: May be fatal if swallowed and enters airways

H315: Causes skin irritation

H318: Causes serious eye irritation

H373: May cause damage to organs through prolonged or repeated exposure

H336: May cause drowsiness or dizziness

H351: Suspected of causing cancer

H360: May damage fertility or the unborn child

H411: Toxic to aquatic life with long lasting effects

PRECAUTIONARY REQUIREMENTS**General Requirements**

P 102 Keep out of reach of children.

P 103 Read label before use.

PreventionP 210 Keep away from heat sources, electrical discharges (sparks), naked (open) flames and ignition sources. **NO SMOKING**P 233 + P 234 Keep original containers tightly closed when not in use and stored in a well ventilated area away from heat and sunlight.
+ P 410

- P 261 Avoid inhaling vapours and spray mists. Ensure there is adequate ventilation at all times.
- P 264 Wash all exposed skin and hair with warm water and soap after use.
- P 270 When using, do not eat, drink or smoke.
- P 273 Avoid release to the environment including waterways, sewage and drains.

The following Risk and Safety Phrases have been allocated for this product in accordance with SAFE WORK AUSTRALIA requirements. The Australian Dangerous Goods Code included.

Risk Phrases R

- 10 Flammable Liquid.
- 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 45 May cause cancer (Category 2).
- 46 May cause genetic heritable damage (Category 1B)
- 52/53 Harmful to aquatic organisms, may cause long term adverse effects to the aquatic environment.
- 65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking Vapours may cause headaches, drowsiness and dizziness.

Safety Phrases S

- 2 Keep out of reach of children
- 7/9 Keep containers tightly closed when not in use and also in a well ventilated area.
- 15/16 Keep away from heat and sources of ignition.
- 20/21 When using, do not eat, drink or smoke.
- 23.3 Do not breathe the vapours.
- 24/25 Avoid skin contact and with the eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 27 Take off immediately all contaminated clothing.
- 28.1 In contact with the skin, wash immediately soap and plenty of water.
- 36/37/38/39 Wear protective clothing, including enclosed footwear, PVC or Neoprene gloves, organic vapour respirator including eye, hair and face protection.
- 45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
- 62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

ADG Classification PAINT RELATED MATERIAL, THINNERS, N.O.S., – immiscible in water, UN 1263, Class 3, HAZCHEM 3[Y], Packing Group III, Initial Emergency Response Guide 15.

SUSMP Classified as a Schedule S 5 poison.

IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

Product Name	THINNER T 306		Code	T 306
Ingredients	Name	CAS Number	Proportion w/w	
	Ethylene Glycol Mono Butyl Ether	111 – 76 – 2	10 – <30.0 %	
	Propylene Glycol Mono Methyl Ether	107 – 98 – 2	1.0 – <10.0 %	
	Solvent Naphtha (Petroleum) Light Aromatic	64742 – 95 – 6	30 – <60.0 %	
	Xylene	1330 – 20 – 7	10 – <30.0 %	
	Ethyl Benzene	100 – 41 – 4	1.0 – <10.0 %	

FIRST AID MEASURES

Inhalation If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim away from the contaminated area to the fresh air. Keep the victim warm and quiet until all symptoms subside. If the victim is not breathing, apply artificial respiration immediately away from the contaminated area.

Ingestion If swallow, and only if the person is conscious, give water to drink. **DO NOT** induced vomiting; seek **URGENT** medical attention if frothing from the mouth occurs.

Eyes If splashed into eyes, hold eyelids apart, and flush the eyes continuously with running for at least 15 minutes. Continue flushing until advised by a doctor.

Skin and Hair If skin and hair contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Continue flushing until advised by a doctor.

First Aid Facilities Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.

Advice to Doctor If poisoning occurs, consult with the Poisons Information Centre {Telephone **13 11 26**}. Have a copy of this material safety data sheet or label available. Treat symptomatically as symptoms may be delayed for several hours after exposure.



FIRE FIGHTING MEASURES

Extinguishing Media and Requirements Carbon Dioxide {CO₂}, alcohol resistant foam, dry chemical or water spray. **DO NOT** use water jets. Bund area with sand to prevent run – off entering waterways, sewage and drains.

Hazardous Decomposition Products On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, soot and smoke, above the boiling point

Flammability Flammable Liquid. Flash Point = 27 °C

Specific Hazards Vapours may form explosive/air mixtures.

Precautions in connection with Fire Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all packages and equipment from the direction of the fire, if safe to do so. Keep upwind.




ACCIDENTAL RELEASE MEASURES

Emergency Procedures. Spills and Leaks Contain all spills and leaks. Avoid contamination with spilt material on surfaces or entering waterways, drains and sewage. Remove all sources of ignition and **NO SMOKING**. Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.

Disposal Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.

Other Precautions Ensure there is adequate ventilation at all times during the cleaning up period.



HANDLING and STORAGE**Precautions for Safe Handling**

Flammable Liquid. Remove all sources of ignition. Wear the recommended Personal Protective Equipment including organic vapour respirator, eye/face protection, protective clothing, gloves and enclosed footwear. Ensure there is adequate ventilation at all times. After use, before eating, drinking or smoking, wash all exposed skin and hair with soap and water.

Conditions of Safe Storage

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS**Exposure Standards MAK**

Ethyl Benzene = 440 mg/m³ Xylene = 350 mg/m³
Solvent Naphtha (Petroleum) Light Aromatic = 100 mg/m³
Ethylene Glycol Mono Butyl Ether = 98 mg/m³
Propylene Glycol Mono Methyl Ether = 370 mg/m³

Exposure Standards STEL

Xylene = 655 mg/m³
Ethylene Glycol Mono Butyl Ether = 242 mg/m³

Biological Limited Values Engineering Controls

There are no known Biological Limited Values have been assigned.

The use of local exhaust ventilation equipment is required. All ventilation equipment must be fitted with flame and explosion proof electrical fittings.

PERSONAL PROTECTION**Inhalation AS –NZS 1715/16**

The wearing of Organic Vapour Respirator **should** be worn at all times during the handling and application period.

Eye AS –NZS 1337

The wearing of safety glasses fitted with side shields **should** be worn at all times during the handling and application period. Do not wear contact lenses.

Gloves AS –NZS 2161

The wearing of Neoprene or PVC gloves **should** be worn at all times during the handling and application period.

Footwear AS –NZS 2210

The wearing of enclosed footwear **should** be worn at all times during the handling and application period.

Clothing AS –NZS 2919


The wearing of anti-static clothing made on natural or synthetic high temperature fibre **should** be worn at all times during the handling and application period

Hearing AS –NZS 1270

Not required.

Other Requirements

Avoid contact with eyes and skin. Avoid inhaling vapours.



PHYSICAL – CHEMICAL PROPERTIES

Appearance	A colourless liquid with a mild odour.	
pH	Not required.	
Vapour Pressure (Butyl Acetate = 1)	Less than 1	
Boiling Point °C	120 – 168 °C	
Density	0.88 {calculated value}	
Solubility in water	Immiscible	
Flash Point °C	27 °C (literature value)	
Flammability	Lower Explosive Limit = 1.0	Upper Explosive Limit = 10.3
Limits		
Auto Ignition °C	250 °C (literature value)	
Volatile Organic Compounds VOC	100 % weight/volume	
Volatile Components	Solvent Naphtha (Petroleum) Light Aromatic, Ethyl Benzene, Xylene, Ethylene Glycol Mono Butyl Ether and Propylene Glycol Mono Methyl Ether.	

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, soot and smoke.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

<i>Health Effects</i>	<i>Risk Phrase</i>	<i>Ethylene Glycol Mono Butyl Ether</i>	<i>Ethyl Benzene</i>	<i>Xylene</i>	<i>Solvent Naphtha(Petroleum) Light Aromatic</i>
Inhalation LC ₅₀ rat	20	Not Known	20 mgm/L.	20 mgm/L.	20 mgm/L.
Dermal LD ₅₀ rabbit	21	220 mgm/kg	2000 mgm/kg	4500 mgm/kg	2000 mgm/kg
Oral LD ₅₀ rat	22	470 mgm/kg	2000 mgm/kg	430 mgm/kg	2000 mgm/kg

Acute Oral Toxicity rat	Moderate toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity rabbit	Moderate toxicity.
Acute Inhalation Toxicity rat	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

TOXICOLOGICAL INFORMATION (CONTINUED)**Health Effects**

Inhalation	The inhalation of vapours may cause acute irritation to the respiratory system. Other symptoms may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination, impaired judgement. Vapours may cause headaches, drowsiness and dizziness
Ingestion	Large quantities may cause nausea and vomiting. Harmful. May cause lung damage if swallowed.
Eyes	May irritate to the eyes, including burning sensation, redness, swelling and/or blurred vision. Also, may cause decreased in colour perception.
Skin	May have degreasing effect on the skin may result in contact dermatitis. Repeated or prolonged exposure may cause skin dryness and cracking.
Carcinogenic	May cause cancer – category 2
Mutagenic	May cause heritable genetic defects – category 1B.
Reproductive	No data available.
Toxicity	

ECOLOGICAL INFORMATION

Environment	Harmful to aquatic organisms, may cause long term adverse effects to the aquatic environment
Persistence/ Degradability	No data available.
Mobility	No data available
Environment Protection	Not Known

**DISPOSAL CONSIDERATIONS**

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents. Crush all small empty containers. Large containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and sewage.

TRANSPORT INFORMATION

UN number	1263		
Proper Shipping Name	PAINT RELATED MATERIAL, THINNERS, NOT OTHERWISE SPECIFIED – immiscible in water.		
Class	3	Subsidiary Risk	Not Required
Packing Group	III		
Emergency Procedures	EP 3305	Initial Emergency Response Guide	15
HAZCHEM	3[<input checked="" type="checkbox"/>]		
IMDG	Not Known		



REGULATORY INFORMATION**Regulatory
Information and
Hazard Category
SUSMP
Classification**

The product is classified as Hazardous Substance in accordance to SAFE WORK AUSTRALIA {HSIS} and Globally Harmonised System as Harmful and Irritant.

Classified as a Schedule S 5 Poison.

OTHER INFORMATION**Emergency
Contact
Disclaimer**

Poisons Information Centre 13 11 26

HiChem Paint Technologies
(03) 9796 3400

Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document