

Hi Chem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 563

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.auwww.hichem.com.au**HAZARD IDENTIFICATION**

The product is classified as Hazardous Substance in accordance with SAFEWORK Australia – Hazardous Substances Information System {HSIS 2013} AUSTRALIA, Global Harmonised System {GHS} and Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

GHS HAZARDOUS STATEMENTS

H 226	Category 3	Flammable Liquid – Flash Point >23° Celsius Boiling Point – ≥ 35 ° Celsius.
H 303	Category 4	Harmful if swallowed
H 312	Category 4	Harmful in contact with the skin
H 316	Category 4	May cause skin irritation
AUH 066	Repeated exposure may cause skin dryness or cracking	
H 320	Category 2B	Causes eye irritation
H 332	Category 4	Harmful if inhaled
H 336	Category 3	May cause drowsiness and dizziness
H 413	Category 4	May cause long lasting harmful effects in the aquatic environment

GHS PRECAUTIONARY STATEMENTS

Statement Type	Statement 'P'	Precautionary Statement Text
General	P 101	Seek medical advice if required
Precautionary	P 102, 103	Carefully read and understand this document during application and handling period.
Prevention	P 233, 234, 235	Keep in original container and tightly closed in a cool dry place when not in use.
	P 241	Ensure all equipment and lighting is explosion proof during the application and handling period.
	P 261	Avoid breathing vapours during manufacturing and handling period.
	P 264	Wash all exposed skin and hair after application and handling period with soap and warm water.
	P 270	Do not smoke, eat or drink during application and handling period.
	P 273	Avoid release to the environment includes drains, sewage and waterways, and atmosphere.
	P 280	The wearing of protective clothes with gloves, vapour mask, face and eye protection during application and handling period.
Response	P 301, 310	If swallowed, rinse the mouth water immediately. Contact the Poisons Information Centre (Telephone 13 11 26) urgently.
	P 303, 313, 362	If on skin or hair, wash all exposed area with plenty of warm water and soap. Seek medical advice if any irritation occurs. Remove all contaminated clothing immediately.

	P 304, 313	If inhaled, removed oneself to fresh air from the contaminated area and keep warm in a comfortable position. Seek medical advice if any symptoms immediately
	P 305, 313	If in eyes, immediately flush with plenty of water. Remove contact lenses if safe to do so if worn. Contact urgent medical advice immediately if any irritation or blurring occurs.
	P 306, 362, 363	If splashed onto clothing, removed all contaminated clothing and wash with plenty of water immediately before reuse
	P 370, 372, 375	If case of fire, use dry sand or earth, or alcohol resistant foam. Containers may explode on heating. If safe to do so, remove all electrical equipment in the direction of fire. Ensure all power supplies are switch off.
	P 380, 381	Consider evacuating the area if the fire presents a threat. Eliminate all ignition sources if safe to do so.
	P 390, 391	Collect and absorb all spillages onto dry sand or earth and placed into clean, dry and labelled containers prior to disposal.
Storage	P 402, 403	Store in a cool, well dry and ventilated place in a Flammable Goods Store and away from direct sunlight.
Disposal	P 501	Dispose carefully unused contents and container(s) to an approved waste disposal site. Further information may be obtained by contacting the Local Statutory Authorities. Ensure all package(s) are labelled as FLAMMABLE LIQUID N.O.S., U.N 1993, CLASS 3, HAZCHEM 3[Y]


Product Usage. MOTORSPRAY Bug and Tar Remover is a powerful solvent based cleaner for the removal of stubborn contaminants from automotive paintwork and chrome surfaces. . For further information contact HICHEM helpdesk. Telephone 03 9796 3034.

IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

Product Name	BUG AND TAR REMOVER	Code	BUG 250
Name		CAS Number	Proportion w/w
	Solvent Naphtha – White Spirit (unspecified)	805 – 41 – 3	95.0 – 100.0 %
	Limonene	68467 – 72 – 3	2.0 – 3.0 %

FIRST AID MEASURES

<i>Inhalation</i>	If the operator feels drowsy, dizzy, tired or experiencing headaches, remove the victim away from the contaminated area to the fresh air. Keep the victim warm and quiet until all symptoms subside. If the victim is not breathing, apply artificial respiration immediately away from the contaminated area.
<i>Ingestion</i>	If swallow, and only if the operator is conscious, give water to drink. DO NOT induced vomiting; seek URGENT medical attention if frothing from the mouth occurs.
<i>Eyes</i>	If splashed into eyes, hold eyelids apart, and flush the eyes continuously with running for at least 15 minutes. Continue flushing until advised by a doctor.
<i>Skin and Hair</i>	If skin and hair contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Continue flushing until advised by a doctor.
<i>First Aid Facilities</i>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<i>Advice to Doctor</i>	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this safety data sheet or label available. Treat symptomatically as symptoms may be delayed for several hours after exposure.

**FIRE FIGHTING MEASURES**

<i>Extinguishing Media and Requirements</i>	Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways, sewage and drains.
<i>Hazardous Decomposition Products</i>	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, soot and smoke, above the boiling point
<i>Flammability</i>	Highly Flammable Liquid. Flash Point = 4 °Celsius
<i>Specific Hazards</i>	Vapours may form explosive/air mixtures.
<i>Precautions in connection with Fire</i>	Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus incorporating an Organic Vapour Respirator and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all packages and equipment from the direction of the fire, if safe to do so Keep upwind.



ACCIDENTAL RELEASE MEASURES

Emergency Procedures. Spills and Leaks


Contain all spills and leaks. Avoid contamination with spilt material on surfaces or entering waterways, drains and sewage. Remove all sources of ignition and **NO SMOKING**. Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.

Disposal

Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.

Other Precautions

Ensure there is adequate ventilation at all times during the cleaning up period.



HANDLING and STORAGE

Precautions for Safe Handling

Flammable Liquid. Remove all sources of ignition. Wear the recommended Personal Protective Equipment including organic vapour respirator, eye/face protection, protective clothing, gloves and enclosed footwear. Ensure there is adequate ventilation at all times. After use, before eating, drinking or smoking, wash all exposed skin and hair with soap and water.

EXPOSURE CONTROLS for 8 hours

Exposure Standards MAK

Limonene = 100 milligram/cubic metre
Solvent Naphtha – White Spirit = 100 milligram/cubic metre

PERSONAL PROTECTION

Inhalation AS –NZS 1715/16

The wearing of Organic Vapour Respirator **should be** worn at all times during the application and handling period.

Eye AS –NZS 1337

The wearing of safety glasses fitted with side shields **should be** worn at all times during the application and handling period. Do not wear contact lenses.

Gloves AS –NZS 2161

The wearing of Neoprene or PVC gloves **should be** worn at all times during the application and handling period.

Footwear AS –NZS 2210

The wearing of enclosed footwear **should be** worn at all times during the application and handling period.

Clothing AS –NZS 2919


The wearing of anti–static clothing made on natural or synthetic high temperature fibre **should be** worn at all times during the application and handling period.

Hearing AS –NZS 1270

Not required

Other Requirements

Avoid contact with eyes and skin at all times. Avoid inhaling vapours.



PHYSICAL – CHEMICAL PROPERTIES

Appearance	A colourless liquid with a pine type odour.	
pH	Not required.	
Vapour Pressure (Butyl Acetate = 1)	Greater than 1	
Boiling Point °C	175 to 185 ° Celsius	
Density	0.78	
Solubility in water	Immiscible	
Flash Point °C	45 ° Celsius (literature value)	
Flammability	Lower Explosive Limit = 1.0	Upper Explosive Limit = 3.5
Limits		
Auto Ignition °C	250 ° Celsius (literature value)	
Volatile Organic Compounds VOC	100.0 % volume/volume	
Volatile Components	Liquid Aliphatic Hydrocarbons	

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, soot and smoke.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

Ingredient	Inhalation <i>LC₅₀ (rat)</i>	Dermal <i>LD₅₀ (rabbit)</i>	Oral <i>LD₅₀(rat)</i>
Limonene	20 mgm/Litre	2000 mgm/kgm	2000 mgm/kgm
Solvent Naphtha – White Spirit	20 mgm/Litre	2000 mgm/kgm	2000 mgm/kgm

Acute Inhalation Toxicity	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
Acute Dermal Toxicity	Low toxicity.
Acute Oral Toxicity	Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which may be fatal.

TOXICOLOGICAL INFORMATION (CONTINUED)**Health Effects – Toxicological and Other Health Information**

Inhalation	No data available
Ingestion	No data available.
Eyes	If in eyes, may cause other symptoms including burning sensation, redness, swelling and/or blurred vision. Also, may cause decreased in colour perception.
Skin	May have degreasing effect on the skin may result in contact dermatitis. Repeated or prolonged exposure may cause skin dryness and cracking.
Carcinogenic	Not carcinogenic in animal studies
Mutagenic	Not mutagenic in animal studies.
Reproductive	No data available..
Toxicity	

ECOLOGICAL INFORMATION

Environment	May cause long lasting harmful effects in the aquatic environment.
Persistence/ Degradability	No data available.
Mobility	No data available
Environment Protection	Not Known

**DISPOSAL CONSIDERATIONS**

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents. Crush all small empty containers. Large containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and sewage

TRANSPORT INFORMATION

UN number	1993		
Proper Shipping Name	FLAMMABLE LIQUID, Not Otherwise Specified.		
Class	3	Subsidiary Risk	Not Required
Packing Group	III		
Emergency Procedures	EP 3305	Initial Emergency Response Guide	15
HAZCHEM	3[Y]E		
IMDG	Not Known		



REGULATORY INFORMATION

**Regulatory
Information and
Hazard Category
SUSMP
Classification**

The product is classified as Hazardous Substance in accordance to SAFE WORK AUSTRALIA {HSIS} and Globally Harmonised System as Harmful and Irritant.

Classified as a Schedule S 5 Poison.

OTHER INFORMATION

**Emergency
Contact
Disclaimer**

Poisons Information Centre 13 11 26

**HiChem Paint Technologies
(03) 9796 3400**

Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document



Version 2.0
HIGH 7748
August 2015