

# RUST-OLEUM® CRAFT & HOBBY ACRYLIC GLITTER BURST PAINT

# **DESCRIPTION AND USES**

Rust-Oleum<sup>®</sup> Craft & Hobby Acrylic Glitter Burst Paint adds sparkle and shimmer to craft and decorative surfaces. The glittering effect intensifies with multiple layer application. Can be applied over a base colour.

Ideal for wood, paper mache, terra cotta and most porous surfaces as well as ceramic bisque and glass.

#### **FEATURES**

- Multi Purpose
- Water-Based

### **PRODUCT**

SKU	DESCRIPTION
327305	Acrylic Glitter Paint Set

# **SET CONTENTS**

SKU	<b>DESCRIPTION (59 ml Bottle)</b>
331315	Glitter Gold
331317	Glitter Silver
331318	Glitter Black

## PRODUCT APPLICATION

#### **APPLICATION CONDITIONS**

Use in a well ventilated area. Use when temperature is between 10- 32°C and humidity is below 85% to ensure proper drying.

#### **SURFACE PREPARATION**

Clean all surfaces with soap and water. Rinse thoroughly Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to fully dry. All surfaces must be dry at time of application. Scrape and wire brush or power tool clean to remove loose rust, scale and deteriorated previous coatings.

Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. The Craft & Hobby Acrylic Glitter Burst Paints are compatible with most coatings, but a test patch is suggested.

# PRODUCT APPLICATION (cont.)

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop

#### **APPLICATION**

Apply only when air and surface temperatures are between 10-32°C and humidity is below 85% to ensure proper drying. Before using, stir thoroughly to ensure any settled pigment is re-dispersed. Avoid painting in direct sunlight or on hot surfaces. Use a good quality synthetic brush. Avoid excessive brushing as this will reduce film thickness and protection. Use light even strokes to ensure an even flow and the smoothest finish.

#### **DRY TIME**

Dry and recoat times are based on 25°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 30 minutes, dry to handle in 2 hours, and fully dry in 8 hours. May be recoated in 3 hours.

#### **CLEAN-UP**

Clean brush and other application tools immediately with soap and water.

Form: ARJ-1464 Rev.: 121217



# RUST-OLEUM® CRAFT & HOBBY ACRYLIC GLITTER BURST PAINT

# PHYSICAL PROPERTIES

			CRAFT & HOBBY ACRYLIC GLITTER BURST PAINT
Resin Type			Modified Waterborne Acrylic Copolymer
Pigment Type			Metalized Polyester
Volatile Organic Compounds		mpounds	<165
Weight	Pe	er Litre	1.0-1.5 kg
Solids	В	y Weight	13.5-17.5%
	В	y Volume	11-14.5%
Recommended Dry Film Thickness (DFT) per Coat			25-50μ (1.0-2.0 mils)
Dry Times at 25°C and 50% Relative Humidity		Touch	30 minutes
	Handle	2 hours	
	Recoat	3 hours	
		Full Cure	8 hours
Shelf Life			5 years
Flash Point			33°C
Safety Information			For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

