



RUST-OLEUM® CRAFT & HOBBY ACRYLIC PAINT

DESCRIPTION AND USES

Rust-Oleum® Craft & Hobby Acrylic Paint ideal for wood, paper mache, plastic, ceramic, metal, fabric, pottery, glass and more.

FEATURES

- Multi Purpose
- Water-Based

PRODUCT

SKU	DESCRIPTION
333317	Acrylic Paint Set

SET CONTENTS

SKU	DESCRIPTION (7.4 ml Bottle)
331285	Black
331286	White
331288	Red
331289	Yellow
331290	Blue
331311	Orange
331312	Gold
331313	Silver
331314	Green

PRODUCT APPLICATION

APPLICATION CONDITIONS

Use in a well ventilated area. Use when temperature is between 10- 32°C and humidity is below 85% to ensure proper drying .

SURFACE PREPARATION

Clean all surfaces with soap and water. Rinse thoroughly. Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to fully dry. All surfaces must be dry at time of application. Scrape and wire brush or power tool clean to remove loose rust, scale and deteriorated previous coatings.

Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. The Craft & Hobby Acrylic Paints are compatible with most coatings, but a test patch is suggested.

PRODUCT APPLICATION (cont.)

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop

APPLICATION

Apply only when air and surface temperatures are between 10-32°C and humidity is below 85% to ensure proper drying. Before using, stir thoroughly to ensure any settled pigment is re-dispersed. Avoid painting in direct sunlight or on hot surfaces. Use a good quality synthetic brush. Avoid excessive brushing as this will reduce film thickness and protection. Use light even strokes to ensure an even flow and the smoothest finish.

DRY TIME

Dry and recoat times are based on 25°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20-30 minutes, dry to handle in 1 hour, and fully dry in 8 hours. May be recoated in 2 hours.

CLEAN-UP

Clean brush and other application tools immediately with soap and water.

	TECHNICAL DATA	RCH-02
	RUST-OLEUM® CRAFT & HOBBY ACRYLIC PAINT	

PHYSICAL PROPERTIES

CRAFT & HOBBY ACRYLIC PAINT		
Resin Type		Waterborne Acrylic
Pigment Type		Varies, depending on colour
Volatile Organic Compounds		<420 g/L
Weight	Per Litre	1.0-1.5 kg
Solids	By Weight	26.5-36.5%
	By Volume	24-28%
Recommended Dry Film Thickness (DFT) per Coat		25-50µ (1.0-2.0 mils)
Dry Times at 25°C and 50% Relative Humidity	Touch	20-30 minutes
	Handle	1 hour
	Recoat	2 hours
	Full Cure	8 hours
Shelf Life		3 years
Flash Point		33°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
email: sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch, 7675 New Zealand
PH: 64 3 347 7770
www.rustoleum.co.nz
Email: info@haydn.co.nz

Form: ARJ-1465
Rev.: 121217