

RUST-OLEUM® CRAFT & HOBBY AIRBRUSH PAINT KIT

DESCRIPTION AND USES

Rust-Oleum[®] Craft & Hobby Airbrush Paint Kit for painting and detailing model kits and personalise skateboards, helmets, bikes and more.

FEATURES

- · Snap and Spray Airbrush
- Propellant included

PRODUCT

SKU	DESCRIPTION
327308	Airbrush Paint Kit

SET CONTENTS

Quantity	DESCRIPTION
1	Airbrush
1	Propellant 170g net
1	Instruction Sheet
1	Air Connector
4	Clip Caps
4	Diptubes
2	Cleaning Wires

COMPANION PAINT

DESCRIPTION	SIZE
Rust-Oleum Craft & Hobby Acrylic Paint	59 ml

PRODUCT APPLICATION

APPLICATION CONDITIONS

Use in a well ventilated area. Use when temperature is between 10- 32°C and humidity is below 85% to ensure proper drying.

SURFACE PREPARATION

Clean all surfaces with soap and water. Rinse thoroughly Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to fully dry. All surfaces must be dry at time of application. Scrape and wire brush or power tool clean to remove loose rust, scale and deteriorated previous coatings.

Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. The Craft & Hobby Acrylic Paints are compatible with most coatings, but a test patch is suggested.

PRODUCT APPLICATION (cont.)

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop

APPLICATION

Apply only when air and surface temperatures are between 10-32°C and humidity is below 85% to ensure proper drying. Before using, stir thoroughly to ensure any settled pigment is re-dispersed. Avoid painting in direct sunlight or on hot surfaces. Use light even coats to ensure an even flow and the smoothest finish.

DIRECTIONS

Hold end of airbrush hose over propellant can and screw on tightly. Insert plastic diptube into clip cap. Always maintain can in upright position when connecting fitting and during use. Inversion of can during use will discharge liquid propellant which may cause frostbite upon skin contact. Remove paint cap and screw clip cap onto paint bottle. Push paint bottle with clip clap into "C" shaped opening on airbrush. Threaded adapter fittings are attached to can by turning clockwise. Clip cap will snap into place and you are ready to paint.

Do not shake can prior to or during use.

To minimize pressure loss during prolonged use, place can in a shallow pan of room temperature water. Remove airbrush adapter fittings from propellant can when not in use.

STORAGE

Store can upright in a cool dry place when not in use.

CLEAN-UP

Remove the bottle and Clip Cap from your airbrush. Wash Clip Caps and Diptubes promptly with the cleaning solution recommended for the paint you are using. Soap and water solution can be used for acrylic paint. Insert the Cleaning Wire into the Clip Cap tip to remove any remaining paint.

Form: ARJ-1467 Rev.: 121417



RUST-OLEUM® CRAFT & HOBBY **AIRBRUSH PAINT KIT**

PHYSICAL PROPERTIES

	CRAFT & HOBBY AIRBRUSH PAINT KIT PROPELLANT	
Propellent	Alkane Hydrocarbons	
Pigment Type	N/A	
Volatile Organic Compounds	N/A	
Vapour Pressure @ 70°F	30-33 PSIG	
Shelf Life	3 years	
Flash Point	-104°C	
Safety Information	For additional information, see SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

Rust-Oleum Australia PTY. LTD.

email: sales@rustoleum.com.au

Eastern Creek, NSW 2766 Australia

Unit 12, 4 Southridge Street

www.rustoleum.com.au

PH: 1 300 784 476



Form: ARJ-1467

Rev.: 121417