



RUST-OLEUM® CRAFT & HOBBY AIR BRUSH PROPELLANT

DESCRIPTION AND USES

Rust-Oleum® Craft & Hobby Airbrush Propellant for painting and detailing model kits and personalise skateboards, helmets, bikes and more.

PRODUCT

SKU	DESCRIPTION
331434	Airbrush Propellant

COMPANION PRODUCTS

DESCRIPTION	SIZE
Rust-Oleum Craft & Hobby Airbrush Paint Kit	N/A
Rust-Oleum Craft & Hobby Acrylic Paint	59 ml

PRODUCT APPLICATION

APPLICATION CONDITIONS

Use in a well ventilated area. Use when temperature is between 10- 32°C and humidity is below 85% to ensure proper drying .

PRODUCT APPLICATION (cont.)

DIRECTIONS

Hold end of airbrush hose over propellant can and screw on tightly. Insert plastic diptube into clip cap. Always maintain can in upright position when connecting fitting and during use. Inversion of can during use will discharge liquid propellant which may cause frostbite upon skin contact. Remove paint cap and screw clip cap onto paint bottle. Push paint bottle with clip cap into "C" shaped opening on airbrush. Threaded adapter fittings are attached to can by turning clockwise. Clip cap will snap into place and you are ready to paint.

Do not shake can prior to or during use.

To minimize pressure loss during prolonged use, place can in a shallow pan of room temperature water. Remove airbrush adapter fittings from propellant can when not in use.

STORAGE

Store can upright in a cool dry place when not in use.

CLEAN-UP

Remove the bottle and Clip Cap from your airbrush. Wash Clip Caps and Diptubes promptly with the cleaning solution recommended for the paint you are using. Soap and water solution can be used for acrylic paint. Insert the Cleaning Wire into the Clip Cap tip to remove any remaining paint.

	TECHNICAL DATA	RCH-05
	RUST-OLEUM® CRAFT & HOBBY AIR BRUSH PROPELLANT	

PHYSICAL PROPERTIES

	CRAFT & HOBBY AIR BRUSH PROPELLANT
Propellant	Alkane Hydrocarbons
Pigment Type	N/A
Volatile Organic Compounds	N/A
Vapour Pressure @ 70°F	30-33 PSIG
Shelf Life	3 years
Flash Point	-104°C
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia PTY. LTD.
Unit 12, 4 Southridge Street
Eastern Creek, NSW 2766 Australia
PH: 1 300 784 476
www.rustoleum.com.au
email: sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.
PO Box 86054
Christchurch, 7675 New Zealand
PH: 64 3 347 7770
www.rustoleum.co.nz
Email: info@haydn.co.nz

Form: ARJ-1469
Rev.: 121417