



# **ZINSSER® BAMBOO OIL**

## **DESCRIPTION AND USES**

Zinsser® Bamboo Oil is a water-based exterior top coat sealer designed specifically for bamboo surfaces. The best way to maintain the condition and lengthen the life of bamboo is to seal it and Zinsser's Bamboo Oil delivers the ultimate protection for your bamboo. Zinsser Bamboo Oil is easy to apply, self-priming and protects against the sun's harsh UV rays. Zinsser Bamboo Oil dries to an enhanced gloss transparent finish.

Recommended For: Exterior bamboo surfaces, both horizontal and vertical. Also great for use on screen fences, gates, cladding and exterior doors and furniture.

## **PRODUCTS**

DESCRIPTION	4 L	10 L
Bamboo Oil Natural	335941	335909
Bamboo Oil Black	335942	335910

## **FEATURES**

- Deep penetrating formula
- UV protection, water repellent
- Dirt & Mould protection

## **PRODUCT APPLICATION**

### **READ ALL DIRECTIONS CAREFULLY BEFORE BEGINNING PROJECT**

#### **SURFACE PREPARATION**

The performance of Zinsser Bamboo Oil depends on the quality of the surface preparation. Do not apply Zinsser Bamboo Oil on wet bamboo as this may cause film defects, such as loss of adhesion and uneven pigmentation.

**NEW BAMBOO SURFACES:** All grease, oil, grime, sap, and other contaminants must be removed with a cleaning solution, such as Zinsser® Deck Bright, using a soft bristle broom or brush.

**PREVIOUSLY COATED BAMBOO:** Remove all solvent based and water-based oils by applying Zinsser® Timber Clean using a stiff bristle broom to scrub the surface and leave on for 5 minutes. Remove with clean water. Use 320 grit sandpaper to sand back painted surfaces to a raw bamboo, or apply Zinsser® Gel Stripper and scour to remove stains, acrylic, polyurethanes etc. Followed by washing with Zinsser® Timber Prep to neutralise the surface (this is very important).

## **PRODUCT APPLICATION (cont.)**

**APPLICATION TIPS:** For best results, apply in temperatures between 23°C and 27°C. Do not apply if humidity is greater than 85% or temperature is below 5°C.

### **APPLICATION**

Make sure bamboo is dry and free of moisture, we recommend applying after bamboo has been exposed to dry weather for a minimum of 3 to 5 days. Apply a thin coat of Zinsser Bamboo Oil onto the bamboo using an industrial coating brush, paint brush, pressure washer (using a fine tip with 1800 PSI) or lint free cloth. Wipe off all excess material with the brush or rag and allow 1-2 hours for curing depending on the weather conditions. For best results, apply 2 coats for bamboo screening and 3 coats for outdoor bamboo furniture

**NOTE:** Colour will deepen with the number of coats applied.

**RECOAT:** Allow 1-2 hours dry time between coats.

**DRY TIME:** Dries to the touch in 5-10 minutes. Zinsser Bamboo Oil will fully cure in 2 hours. Dry times will be slower in cold, damp conditions or if applied in high humidity

**CLEAN UP:** Clean up with soap and water.

**STORAGE:** Store in a cool, dry place.

**NOTE:** Not for interior use.

		<b>TECHNICAL DATA</b>	<b>ZNR-67</b>
		<b>ZINSSER®</b> <b>BAMBOO OIL</b>	

## PHYSICAL PROPERTIES

		<b>BAMBOO OIL</b>
<b>Resin Type</b>		Modified Acrylic Emulsion
<b>Pigment Type</b>		Iron Oxide
<b>Solvents</b>		Butoxy ethanol
<b>Weight</b>	<b>Per Litre</b>	1.01-1.05 kg
<b>Solids</b>	<b>By Weight</b>	15-20%
	<b>By Volume</b>	15-20%
<b>Volatile Organic Compounds</b>		<25 g/l
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		0.4 mils
<b>Wet Film to Achieve DFT (Unthinned material)</b>		1 mil
<b>Practical Coverage at Recommended DFT (assume 15% material loss)</b>		12.5-16.7 m <sup>2</sup> /l
<b>Dry Times at 25°C and 50% Relative Humidity</b>	<b>Touch</b>	5-10 minutes
	<b>Handle</b>	20-30 minutes
	<b>Recoat</b>	1-2 hours
<b>Shelf Life</b>		1 year
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia PTY. LTD.  
Unit 12, 4 Southridge Street  
Eastern Creek, NSW 2766 Australia  
PH: 1 300 784 476  
[www.rustoleum.com.au](http://www.rustoleum.com.au)  
email: [sales@rustoleum.com.au](mailto:sales@rustoleum.com.au)

HAYDN BRUSH CO. LTD.  
PO Box 86054  
Christchurch, 7675 New Zealand  
PH: 64 3 347 7770  
[www.rustoleum.co.nz](http://www.rustoleum.co.nz)  
Email: [info@haydn.co.nz](mailto:info@haydn.co.nz)

Form: ARJ-1511  
Rev.: 020818