RUST-OLEUM®

MARINE COATINGS

# MARINE COATINGS ANTI-SLIP ADDITIVE

## **DESCRIPTION AND USES**

Rust-Oleum<sup>®</sup> Marine Coatings Anti-Slip Additive easily mixes with latex or oil-based paints to provide a skid-resistant surface on wood, metal, fiberglass and concrete. Anti-Slip Additive is a pumice material which adds a slight surface texture and promotes skid resistance of coatings used on floors, decks, stairs, ramps, patios, boat jettys and walkways. Anti-Slip Additive will not change color or the performance properties of the paint.

## **APPEARANCE**

Off-White particles or granules

#### **PRODUCTS**

SKU (1/2 pint) Description

207009 Anti-Slip Additive

### RECOMMENDED COATINGS

Add to any floor coating with a dry film thickness of 8 mils or less.

## PRODUCT APPLICATION

Add one container (½ pint) of Anti-Slip Additive per quart of coating to be applied. Mix thoroughly into the paint until a uniform and consistent mixture is achieved. Stir often during use to prevent settling. Follow application directions on the Topside Paint. Application of a coating containing the Anti-slip Additive by airless spray is not recommended.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 877-385-8155 www.rustoleum.com Form: GDH-160 Rev.: 090313