

Product/Technical Data Sheet (TDS)

Seam Sealer

Description

MOTOSPRAY SEAM SEALER fills gaps and seals against moisture, dust and rust.

Uses

SEAM SEALER is a flexible, fast setting sealant for sealing spot welded joints or bolted coach joints such as floor pans and wheel arches. Suitable for filling gaps in lap joints and seams to protect against moisture and rust, ideal for sealing tail light and headlight openings and much more.

Properties

Colour - Black

Does not sag or flow on vertical surfaces.

Excellent adhesion to all surfaces.

Suitable Substrates

Bare steel, primed or fully painted surfaces.

Surface Preparation

Clean surface with *PREPWASH* to remove wax, grease, oil and silicone and ensure surface is dry.

Application

Apply a uniform amount of *SEAM SEALER* always brushing in the same direction and allow brush marks to duplicate original equipment manufacturer appearance

Drying Time

Surface will skin in 15 minutes and can be painted in 30-40 minutes (depending on thickness and drying conditions)

Clean up

PREPWASH.

Storage

Store in a cool dry place. Always replace the lid securely after use.

Safety

See material safety data sheet.

Standard Packages and Product Codes

1 litre BSS1

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.