



**PAINTER'S TOUCH PLUS®
PAINT + PRIMER**

DESCRIPTION AND USES

Rust-Oleum® Painter's Touch Plus® contains breakthrough technology that provides excellent coverage and durability on wood, metal, plastic, wicker and more. It covers surfaces with less spray passes, allowing projects to be completed faster and easier. Painter's Touch Plus features an advanced spray system that allows you to spray in any direction, even upside down. A comfort spray tip with a wider finger pad to reduce fatigue caused by continuous spraying.

Tip: Some plastics made of polyethylene such as Little Tikes®* children's products are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first. Not for use on galvanised metal.

PRODUCTS

SKU	DESCRIPTION
300322	Gloss Black
300323	Gloss White
300324	Gloss Red
300325	Gloss Rose Petal
300326	Gloss Palest Pink
300327	Gloss Saddle Brown
300328	Gloss Crimson
300329	Gloss Pine Green
300330	Gloss Lime Green
300331	Gloss Café Brown
300332	Gloss Orange
300333	Gloss Island Blue
300334	Gloss Canary Yellow
300396	Gloss Royal Blue
300397	Gloss Pewter
300398	Gloss Purple
300399	Gloss Grass Green
300400	Gloss Grey Mist
201417	Gloss Pink Peony
333291	Gloss Modern Mint
333293	Satin Silver Lilac
333295	Satin Lagoon
333296	Satin Ink Blue
333297	Satin Granite
300335	Satin Black
300336	Satin Java Brown
300337	Satin French Vanilla

*Little Tikes® is a registered trademark of the Little Tikes Company.

PRODUCTS (cont.)

SKU	DESCRIPTION
300338	Satin Ivory Tusk
300339	Satin Sea Blue
300340	Satin Dazzle Red
300411	Satin Lavender
306593	Satin White
300342	Flat Black
300412	Flat White

PRODUCT APPLICATION

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 10°C and 32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. Do not apply to galvanised metal. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist..

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces to create a surface profile.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

PRIMING

Use of a Painter's Touch Plus Primer provides excellent adhesion and hiding and is especially recommended for bare wood and metal. The following primers are recommended:

SKU	DESCRIPTION
300345	Primer Grey
300346	Primer White

PAINTER'S®
*Touch+***PAINTER'S TOUCH PLUS®**
PAINT +PRIMER**PRODUCT APPLICATION (cont.)****PAINTING**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 25-40 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

DRY & RECOAT TIMES

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, and is fully dry in 24 hours. Apply a second coat or clear coat within 1 hour or after 48 hours. Apply the clear in 2-3 light coats a few minutes apart. NOTE: On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

PRODUCT APPLICATION (cont.)**COVERAGE**

Each can will cover up to 4.5 m² depending on surface.

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with mineral turps. Throw away empty can in garbage pickup. Do not burn or puncture the can even when empty.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert a pin or other object into the stem.

PAINTER'S Touch+	TECHNICAL DATA	PTP-01
PAINTER'S TOUCH PLUS® PAINT +PRIMER		

PHYSICAL PROPERTIES

		PAINTER'S TOUCH PLUS PAINT+PRIMER
Resin Type		Modified Alkyd
Pigment Type		Varies with Color
Solvents		Acetone, n-Butane, Naphtha, Xylene, Aromatic Hydrocarbons
MIR		Gloss & Non-Flats – 0.95 Max Flats – 0.80 Max
Fill Weight		340 g
Recommended Dry Film Thickness (DFT) Per Coat		(25-50µ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Up to 4.5 m ² /can
Dry Times at 21-27°C and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 48 hours
Dry Heat Resistance		93°C
Shelf Life		5 years
Flash Point		-104°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.