

	<b>TECHNICAL DATA</b>	<b>PTP-02</b>
	<b>PAINTER'S TOUCH PLUS® METALLIC ENAMEL SPRAY</b>	

## DESCRIPTION AND USES

Rust-Oleum® Painter's Touch Plus® Metallic provides a rich, brilliant finish on wood, metal and more. Painter's Touch Plus® Metallic will provide a shiny metallic look to picture frames, candle holders, holiday crafts and more. This leafing metallic is for use on interior decorative items only.

## PRODUCTS

SKU	DESCRIPTION
306591	Metallic Gold
306609	Metallic Silver
201047	Metallic Copper
201053	Metallic Champagne

## PRODUCT APPLICATION

**READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.**

### PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 10°C and 32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. Do not apply to galvanised metal. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist..

### SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces to create a surface profile.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

### PRIMING

Use of a Painter's Touch Plus Primer provides excellent adhesion and hiding and is especially recommended for bare wood and metal. The following primers are recommended:

SKU	DESCRIPTION
300345	Primer Grey
300346	Primer White

## PRODUCT APPLICATION (cont.)

### PAINTING

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 25-30 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Rust-Oleum Metallics are not recommended for outdoor use. Do not use near open flame.

### DRY & RECOAT TIMES

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 15 minutes, to handle in 30 minutes and is fully dry in 24 hours. Apply a second coat within 1 hour or after 24 hours. A clear coat finish is not recommended.

### COVERAGE

Each can will cover up to 4.5 m<sup>2</sup> depending on surface.

### CLEAN-UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean-up wet paint with mineral turps. Throw away empty can in garbage pickup. Do not burn or puncture the can even when empty.

### CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert a pin or other object into the stem.

	<b>TECHNICAL DATA</b>	<b>PTP-02</b>
<b>PAINTER'S Touch+</b>	<b>PAINTER'S TOUCH PLUS® METALLIC ENAMEL SPRAY</b>	

## PHYSICAL PROPERTIES

		PAINTER'S TOUCH METALLIC ENAMEL SPRAY
Resin Type		Proprietary Alkyd
Pigment Type		Aluminum
Solvents		n-Butane, Toluene, Xylene, Aromatic Hydrocarbons
MIR		1.25 Max
Fill Weight		312 g
Recommended Dry Film Thickness (DFT) Per Coat		(25-50μ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Up to 4.5 m <sup>2</sup> /can
Dry Times at 21-27°C and 50% Relative Humidity	Touch	15 minutes
	Handle	30 minutes
	Recoat	Within 1 hour or after 24 hours
Dry Heat Resistance		93°C
Shelf Life		5 years
Flash Point		-96°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



**MANUFACTURED BY:** Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, Illinois 60061, USA. **IMPORTED AND DISTRIBUTED BY: AUSTRALIA:** Rust-Oleum Australia PTY. LTD. Unit 12, 4 Southridge Street Eastern Creek NSW 2766 Australia, PH: 1 (300) 784 476, email: sales@rustoleum.com.au, www.rustoleum.com.au **NEW ZEALAND:** Haydn Brush CO. LTD. PO Box 86054, Christchurch 7675 NZ, PH: 64 3 347 7770, email: info@haydn.co.nz, www.rustoleum.co.nz **SOUTH AFRICA:** Rust-Oleum South Africa PTY. LTD. P.O. Box 400 Randvaal 1873 Gauteng, South Africa, PH: (016) 365 5120, email: info@spraymate.co.za, www.rustoleum.co.za

Form: GDH-914  
Rev.: 110817