



**FABRIC  
WATER REPELLING TREATMENT**

**DESCRIPTION AND USES**

Rust-Oleum® NeverWet™ Fabric is a one-step, superhydrophobic, water repelling treatment designed to keep items dry longer. This crystal clear formula allows fabrics to breathe, while dramatically repelling water from the surface. NeverWet Fabric preserves outdoor items against damaging moisture without changing the look or feel of the fabric.

NeverWet Fabric is ideal for use on leather, suede, polyester, cotton/polyester blends and canvas fabrics. It is suitable for use on shoes, patio furniture, backpacks, gloves, camping gear and more.

**FEATURES**

- Repels water
- Breathable
- Invisible protection

**PRODUCTS**

SKU	Description
289372	NeverWet Fabric

**SPRAYING CONDITIONS**

Use outdoors or in a well ventilated area. Use when temperature is above 10°C and humidity is below 85% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Apply to clean, dry articles.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Do not shake. A test spray is recommended to obtain a feel for the spray pattern. Test in an inconspicuous area before application for colorfastness. NeverWet Fabric is odourless when dry. Rotate nozzle to “ON” position. Hold the spray bottle 30-40 cm from surface and coat the entire object until wet. Do not soak or allow to puddle. If bubbles appear, lightly dab with a clean, lint-free rag. Re-apply seasonally or when needed. **Note:** Hydrophobicity is dependent on textile. **Do not use near open flame.**

**DRY & RECOAT**

Dry and recoat times are based on 21°C and 50% relative humidity and will vary depending of the fabric. The coating will be odourless when dry. Allow to dry for 24 hours before exposing to water.

**REMOVAL**

If you wish to remove the NeverWet Fabric Water Repelling Treatment, scrub the coated area with soap and water until the superhydrophobic effect is gone.

**CLEAN-UP**

When finished spraying, wipe off tip before storing. Properly discard empty container.

**TECHNICAL DATA****NEVERWET™ FABRIC WATER REPELLING TREATMENT****PHYSICAL PROPERTIES**

		NEVERWET FABRIC
Resin Type		Silicone
Pigment Type		NA
Solvents		Mineral Spirits
Weight per Liter		0.79 kg
Fill Weight		325 mL
VOC		710 g/l
Practical Coverage at Recommended DFT (assumes 15% material loss)		Coverage will vary depending on fabric 5.5 m <sup>2</sup> on smooth/light fabrics to 2 m <sup>2</sup> on textured/heavy fabrics
Dry Times at 21-27°C and 50% Relative Humidity	Touch	Varies depending on fabric
	Handle	Varies depending on fabric
	Full Cure	Allow to dry 24 hours before exposing to water
Shelf Life		2 years
Flash Point		24°C
Safety Information		For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia Pty, Ltd.  
Unit 12, 4 Southridge Street  
Eastern Creek, NSW 2766  
PH: 1 300 784 476  
www.rustoleum.com.au  
email: sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.  
PO Box 4325  
Christchurch, New Zealand  
PH: 64 3 384 7770  
email: mail@haydn.co.nz

Form: GDH-587  
Rev.: 121614