

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®  
PEEL COAT**

**PEEL COAT  
REMOVABLE RUBBER COATING**

**DESCRIPTION AND USES**

Rust-Oleum® Peel Coat is a rubberized coating designed to provide comfort and protection. This product can be applied in just a few spray passes and peeled off when desired. It can be used on metal, wood, glass, rubber, concrete, fiberglass, aluminum and more.

**PRODUCTS**

SKU	Description
279168	Matt Black
279169	Matt White
282309	Matt Dark Grey
282400	Silver
282401	Matt Red

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Apply when temperature is between 10-32°C (50-90°F) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants from the area to be coated by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. A test spray on cardboard is recommended to obtain feel for spray pattern. Hold can upright 20-30 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Care should be taken to keep the can in motion and spray at proper distance to avoid sagging. Apply 4 or more light coats, 5 minutes apart, followed by 1 medium coat to achieve a smooth final finish. More coats will result in a thicker coating which is easier to peel off. **Do not use near open flame.**

**DRYING TIME**

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20 minutes, to handle in 1 hour and is fully dry in 24 hours.

**PEELING OFF**

You can peel the film off once the coating has fully cured, typically in 24 hours. Mineral turps may assist in the removal of film in intricate areas.

**CLEAN UP**

When finished spraying, clear nozzle by turning can upside down and pushing spray button for 5 seconds. Wipe off tip before storing. Clean-up wet paint with mineral turps. Otherwise allow paint to dry and then peel it off. Properly discard empty container. Do not puncture the can, burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not stick pin or other object into the stem.

**TECHNICAL DATA**

**PEEL COAT REMOVABLE RUBBER COATING**

**PHYSICAL PROPERTIES**

Physical Properties		PEELCOAT REMOVABLE RUBBER COATING
Resin Type	Aliphatic Hydrocarbon	
Pigment Type	NA	
MIR	1.30 Max	
Fill Weight	312 grams	
Solvents	Acetone, Methyl Acetate, Xylene	
Recommended Dry Film Thickness(DFT) Per Coat	25-50µ (1.0-2.0 mils)	
Practical Coverage at Recommended DFT (assumes 15% material loss)	Varies depending on type and porosity of surface	
Dry Times at 70°F (21°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Full Cure	24 hours
Shelf Life	5 years	
Flash Point	-156°F (-104°C)	
Safety Information	For additional information, see MSDS.	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.