

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®**WOOD STAIN
ONE COAT****DESCRIPTION AND USES**

Rust-Oleum® Wood Stain is a premium, high performance stain enhanced with nano pigments and soya oil for exceptional color clarity. Combined, the innovative formula creates rich, one coat coverage and one hour dry time. No wood conditioner is required. This advanced formula provides beautiful results 3X faster than traditional wood stains. Top coat your project with Rust-Oleum Varnish for long-term protection and durability. Rust-Oleum Wood Stain can be used on all interior wood projects including furniture, cabinets, doors and trim, floors and paneling.

FEATURES

- Achieve colour in one coat
- Dries in one hour
- 75% more coverage

PRODUCTS

SKU (946 mL)	Description
310397	Antique white
310398	Barn Red
310399	Bleached Blue
310400	Worn Navy
310551	Rustic Sage
310552	Vintage Aqua

PRODUCT APPLICATION**SURFACE PREPARATION**

Surfaces must be clean, dry and sound. Remove any existing finishes with sandpaper or stripper. Prepare bare wood for staining by sanding in the direction of the grain. Begin with #120 grit sandpaper and progress through #150 and #180 grits. Before staining, remove all sanding dust with a vacuum or tack rag and dirt, grease, oil or glue with a clean rag dampened with mineral turps.

PRODUCT APPLICATION (cont.)**TESTING COLOR**

Be sure to test your stain to verify the desired color. To test, follow Stain Application instructions and apply the stain in an inconspicuous area.

APPLICATION

Shake container and stir before use. Stir the material thoroughly and often during use. For best results, use when temperatures are between 16-32°C. Allow longer dry times for damp, humid days. Apply one coat of stain liberally with a brush or a clean lint-free rag. Allow the stain to penetrate for 3-5 minutes; then remove excess stain by wiping with a rag in the direction of the grain. Only one coat of stain is required. Removal of all excess material is essential to ensure proper dry time and proper adhesion of the topcoat.

DRY TIME

Dry times are based on 21°C and 50% relative humidity. Allow longer dry times for damp, humid days. Darker colours may require a slightly longer dry time.

PROTECTING THE WOOD

To complete your wood project and provide long term protection, finish with any varnish depending on your project needs. A varnish can be applied 1 hour after stain application.

COVERAGE

Each container will cover approximately 25m² per 946 mL.

CLEAN-UP

Clean application tools and equipment with mineral turps.

TECHNICAL DATA

WOOD STAIN

PHYSICAL PROPERTIES

Resin		Urethane Modified Alkyd
Pigment Type		Inorganic Pigments
Solvents		Mineral Turps
Weight	Per Litre	0.87-1.02 kg
Solids	By Weight	34.7-51.4%
	By Volume	26.5-36.2%
Volatile Organic Compounds		<550 g/l
Recommended Dry Film Thickness (DFT) Per Coat		12.5-25µ
Wet Film to Achieve DFT (unthinned material)		37.5-100µ
Practical Coverage at Recommended DFT (assumes 15% material loss)		25 m ² /container Varies with type and porosity of wood
Dry Times at 21-27°C and 50% Relative Humidity	Topcoat Ready	1 hour
	Full Cure	8 hours
Shelf Life		3 years (unopened)
Flash Point		40°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.