



# WIPE NEW® RECOLOUR™ SMALL PROJECT WIPE

## DESCRIPTION AND USES

Rust-Oleum® ReColour™ by Wipe New® is a wipe-on clear coat that instantly brings back the original colour and shine to faded plastic, acrylic, fiberglass, metallic and vinyl surfaces, and protects the new finish from harsh elements. It is ideal for use on small projects such as mailboxes, shutters, light fixtures and more.

## FEATURES

- Instantly restores original colour and shine
- Repels dirt and water
- Provides UV protection
- Easier than painting

## PRODUCT

| SKU    | DESCRIPTION                 |
|--------|-----------------------------|
| 333659 | ReColour Small Project Wipe |

## PRODUCT APPLICATION

### READ ALL INSTRUCTIONS PRIOR TO USE

### APPLICATION CONDITIONS

Use when temperatures are between 4°C and 32°C. Use in well ventilated and covered areas away from the sun. Do not apply ReColour to hot surfaces or in direct sunlight. Ensure surface is clean, dry and cool to ambient temperature before applying Wipe New.

### SURFACE PREPARATION

Clean all surfaces intended for application at the same time and allow them to dry completely prior to application of ReColour.

**PLASTIC/VINYL/LEATHER:** Wash with soap and water or a mild degreaser and scrub with a brush to get ingrained dirt out of all the tight areas. Make sure the brush is appropriate for cleaning the surface without damage. If the surface has been treated before with waxes, conditioners, or silicone-based products, then use a degreaser to remove all remnants of the previously used products.

## PRODUCT APPLICATION (cont.)

### SURFACE PREPARATION (cont.)

**METAL:** New metal surfaces that are being coated for corrosion protection can be wiped down with a dry rag to remove dust prior to application of ReColour. Most metallic surfaces that have been exposed to the environment will need to be washed with soap and water or a mild degreaser and scrubbed with a brush to get ingrained dirt out of all the tight areas. Non-painted metallic surfaces that have been exposed to the outdoors and have a bit of surface mineralisation (ex: brass, zinc, stainless steel surfaces, etc.) can be washed and dried with soap and water and then further prepared with a light scrubbing from steel wool to remove the surface mineralisation. For best results, do a final wipe down using an acetone saturated microfibre cloth to remove all remaining residue.

### APPLICATION

Ensure you are in a well ventilated area and the surface intended for application is completely dry. Wearing the chemical resistant gloves, tear open the Wipe-It™ packet, pull out the applicator cloth and carefully coat the surface in a single wipe, from one row to the next with a slight overlap (like mowing a lawn) until the surface is completely coated.

It is NOT necessary to scrub or buff the surface. Doing so will lead to undesirable results and product waste.

### DRY TIME

The surface will dry to touch in about 1 hour and will be fully cured in 24 hour. Allow treated surface to cure for 24 hours before exposure to moisture (rain, dew, sprinklers, etc.). You may cover a treated surface with a tarp after the initial 1 hour cure to protect from rain and/or dew.

### COVERAGE

One Rust-Oleum Wipe New ReColour Small Project Wipe covers up to 1.4 m<sup>2</sup>.

### DISPOSAL

When finished, set the applicator cloth in a location out of the reach of children and allow it to dry completely prior to discarding (a few hours).

|                                                                                   |                                                         |               |
|-----------------------------------------------------------------------------------|---------------------------------------------------------|---------------|
|                                                                                   | <b>TECHNICAL DATA</b>                                   | <b>WNW-15</b> |
|  | <b>WIPE NEW® RECOLOUR™</b><br><b>SMALL PROJECT WIPE</b> |               |

## PHYSICAL PROPERTIES

| WIPE NEW RECOLOUR SMALL PROJECT WIPE           |                                                                          |          |
|------------------------------------------------|--------------------------------------------------------------------------|----------|
| Resin Type                                     | Proprietary                                                              |          |
| Pigment Type                                   | NA                                                                       |          |
| Solvents                                       | 1-Chloro-4-(Trifluoromethyl) Benzene                                     |          |
| Volatile Organic Compounds                     | <150 g/l                                                                 |          |
| Practical Coverage                             | One Wipe New ReColour Small Project Wipe covers up to 1.4 m <sup>2</sup> |          |
| Dry Times at 21-27°C and 50% Relative Humidity | Touch                                                                    | 1 hour   |
|                                                | Full Cure                                                                | 24 hours |
| Shelf Life                                     | 5 years                                                                  |          |
| Flash Point                                    | 37°C                                                                     |          |
| Safety Information                             | For additional information, see SDS                                      |          |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia PTY. LTD.  
Unit 12, 4 Southridge Street  
Eastern Creek, NSW 2766 Australia  
PH: 1 300 784 476  
[www.rustoleum.com.au](http://www.rustoleum.com.au)  
email: [sales@rustoleum.com.au](mailto:sales@rustoleum.com.au)

HAYDN BRUSH CO. LTD.  
PO Box 86054  
Christchurch, 7675 New Zealand  
PH: 64 3 347 7770  
[www.rustoleum.co.nz](http://www.rustoleum.co.nz)  
Email: [info@haydn.co.nz](mailto:info@haydn.co.nz)

Form: ARJ-1450  
Rev.: 121117