

WIPE NEW[®] GLASS TREATMENT

DESCRIPTION AND USES

Glass Treatment by Wipe New[®] is a long lasting treatment that repels nature's worst elements- water, mud, dirt and more, from glass surfaces. The crystal clear, haze-free formula will increase visibility and safety when driving in the poorest weather conditions. The innovative, wipe on technology makes for a quick and easy application.

Wipe New Glass Treatment is great for use on additional automotive glass surfaces such as side mirrors, side windows and rear windows.

In the home, Wipe New Glass Treatment can be used on glass shower doors and ceramic tiles to help prevent soap scum build up and hard water stains.

FEATURES

- Repels water, rain, mud and dirt
- · Improves visibility while driving in poor weather conditions
- Crystal clear, haze-free formula
- Easy-to-use, wipe on application
- Protects through 100 car washes

PRODUCT

SKU 333657 DESCRIPTION

Wipe New Glass Treatment

PRODUCT APPLICATION

APPLICATION CONDITIONS

Use when temperatures are between 10°C and 32°C. Use in well ventilated and covered areas away from the sun. Ensure the glass surface is clean, dry and cool to ambient temperature before applying Wipe New Glass Treatment.

SURFACE PREPARATION

Wipe New Glass Treatment is to be used on glass surfaces only. For best results, clean the glass surface with a glass cleaner to remove any contaminates from the surface. Follow the cleaner instructions for best results. Wipe New Glass Treatment is NOT recommended for plastic surfaces.

PRODUCT APPLICATION (cont.)

APPLICATION

Wearing the included nitrile gloves, tear open the Wipe New Glass Treatment Wipe-It packet. **Note:** The Wipe-It packet will be heavily saturated in order to cover the glass surface with two coats.

In a circular motion, buff the Wipe-It onto the glass surface until the entire glass surface has been covered. Once the glass surface is completely covered, let the treatment sit for 5 minutes. After the treatment has sat for 5 minutes, the glass surface will appear slightly hazed.

Then, in a circular motion, buff off the treatment using the included dry microfibre buffing cloth. Wait 10 minutes before applying the recommended second coat. Apply a second coat of Wipe New Glass Treatment with the existing, presaturated cloth using the same technique.

During the application, it is recommended to re-fold the Wipe-It to maintain cloth saturation.

IMPORTANT! If a slight haze or shine still remains after removing the second coat, use a damp, clean cloth or paper towel to aid in the removal of any remnants.

To fully remove Wipe New Glass Treatment, use a soft soap scrub with cold water and wipe the glass until the coating is removed.

COVERAGE

One Wipe-It contains enough Glass Treatment to treat 9.3 m^2 with two coats. It is recommended to apply two coats.

DISPOSAL

When finished, set the applicator cloth in a location out of the reach of children and allow it to dry completely prior to discarding (a few hours).

WNW-18



WIPE NEW[®] GLASS TREATMENT

PHYSICAL PROPERTIES

		WIPE NEW GLASS TREATMENT
Resin Type		Polydimethylsiloxane
Solvents		Isopropyl Alcohol, Methyl Ethyl Ketone
Volatile Organic Compounds		<570 g/l
Practical Coverage		Two coats will cover 9.3 m ²
Dry Times at 21- 27°C and 50% Relative Humidity	Touch	NA
	1 st Coat	Buff off 1 st coat after 5 minutes; wait 10 minutes and apply 2 nd coat
	2 nd Coat	Buff off 2 nd coat after 5 minutes
	Full Cure	10 minutes
Shelf Life		2 years
Flash Point		-5°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia PTY. LTD. Unit 12, 4 Southridge Street Eastern Creek, NSW 2766 Australia PH: 1 300 784 476 www.rustoleum.com.au email: sales@rustoleum.com.au HAYDN BRUSH CO. LTD. PO Box 86054 Christchurch, 7675 New Zealand PH: 64 3 347 7770 www.rustoleum.co.nz Email: info@haydn.co.nz

Form: ARJ-1453 Rev.: 121117