



SUREGRIP® BORDER ADHESIVE FOR PAINTED SURFACES

DESCRIPTION AND USES

SureGrip® Border Adhesive for Painted Surfaces is a ready-to-use, clear adhesive formulated for hanging all pre-pasted and non-pasted borders over painted or primed surfaces. Apply this adhesive to pre-pasted and non-pasted paper-backed borders over painted or primed surfaces.

SureGrip Border Adhesive for Painted Surfaces is not intended for hanging pre-pasted or non-pasted borders over existing vinyl wallcoverings or extremely rough surfaces such as concrete blocks or stucco. See "Existing Vinyl Wallcovering or Rough Surfaces" under Product Application in next column for recommendations.

PERFORMANCE CHARACTERISTICS

- For hanging any pre-pasted borders
- Provides excellent adhesion
- Dries clear, non-staining

PRODUCTS

SKU	Container Size
69684	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

All walls must be clean, dry, sound and free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Remove old or loose wallcovering and residual wallcovering adhesive with DIF® Wallpaper Stripper. Repair unsound surfaces. Seal loose paint or damaged drywall and cured skim coats with Gardz® High Performance Sealer as needed.

MOLD & MILDEW

Eliminate pre-existing mold and mildew by washing the affected area with a solution of ¼ cup of Clorox® bleach to 1 gallon of water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning agents to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

DRYWALL

Wipe down with a damp cloth to remove residual joint compound dust prior to priming.

PLASTER

New plaster must age at least 90 days before hanging wallcovering. Prime with Bulls-Eye 1-2-3 Primer.

PRODUCT APPLICATION (cont.)

GLOSSY SURFACES

Glossy paint, paneling, metal, glass, plastic and other glossy surfaces should be primed with ShieldZ® Universal Plus Wallcovering Primer, ShieldZ® Clear Acrylic Wall Size or ShieldZ® Oil-Base Wallcovering Primer prior to wallcovering installation. Metal surfaces should be primed with rust inhibiting Bulls-Eye® 1-2-3 Primer.

EXISTING VINYL WALLCOVERING or ROUGH SURFACES

This product is not intended for hanging borders over existing wallcoverings or extremely rough surfaces such as concrete blocks or stucco. For installations over wall coverings, use SureGrip® Border Adhesive for Wallpapered Surfaces, SureGrip® Universal Wallcovering Adhesive or SureGrip® 127 Vinyl over Vinyl Wallcovering Adhesive.

TEXTILES and DELICATE BORDERS

Take special care to keep the adhesive off the face of the wallpaper. Some wallpaper can be stained by water alone. Test for stain resistance prior to installation and hang according to manufacturer's instructions.

APPLICATION

Use only when temperature is between 50-100°F (10-38°C) and the relative humidity is less than 85%. For non-pasted borders, use full strength. For pre-pasted borders, thin with a maximum of 4 ounces of water per quart. Using a brush or roller, apply liberally to the back of the border. Book and hang wallcovering according to the manufacturer's instructions.

COVERAGE

One quart of adhesive will hang 8-12 border spools. Spread rate may differ with various wallcoverings.

DRY TIME

Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.

CLEAN-UP

Remove excess adhesive on or around the border immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

TOOL CLEAN-UP

Clean tools with warm water.

STORAGE

Protect from freezing. Always keep the container tightly closed and store in a cool dry place at temperatures between 40-100°F (4-38°C).



TECHNICAL DATA

SUREGRIP® BORDER ADHESIVE FOR PAINTED SURFACES

PHYSICAL PROPERTIES

	BORDER ADHESIVE for PAINTED SURFACES
Resin Type	Starch-based Border Adhesive
Solvents	Water
Appearance	Clear
Odor	Mild
Solids by Weight	22.5-24.5%
Volatile Organic Compounds (when mixed with water)	<10 g/l (0.083 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)	Coverage depends on the surface conditions and thickness of application.
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.
Shelf Life	1 year
Flammability	Non-flammable
Safety	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.